



**WEVER & DUCRÉ**  
LIGHTING

# BLIEK

## ROUND petit trimless 1.0

164561B3

Project

Type

Notes

Quantity

Date

### GENERAL

Ceiling , Semi-Recessed

Tilt max 60°

Rotation 355°

Black Matt

RAL 9005<sup>a</sup>

IP20

IC rated

Interior

Output: 495 lm

CIE flux code: 99 100 100 100 100

### LED

2700 K

CRI ≥ 90

L70 / 55000h

2 SDCM

### OPTICAL

Beam angle 31°

### ELECTRICAL

excl. driver

17 V

LED Inset 6.0 W

Class 3

350 mA

### PHYSICAL

Diameter 35 mm

Height 55 mm

0.17 kg

alu plasterkit

### CUTOUT

Diameter 78-80 mm


Recessed depth 80 mm

12,5, 15,25

<sup>a</sup> Color may deviate slightly due to production conditions.



Round ceiling recessed downlight made from die-cast aluminium; adjustable; surface Black Matt; powder coated, matt texture; RAL 9005; inner ring black; with COB (Chip on Board) technology for maximum efficiency; light colour 2700 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; beam angle 31°; 355° rotatable and 60° tiltable; degree of protection IP20; PC3; IC rated; driver not included; to be combined with the plasterkit suitable for ceiling thickness; optional honeycomb louver available, to reduce glare; light source replaceable by an authorized professional;






WEVER & DUCRÉ  
LIGHTING

# BLIEK ROUND petit trimless 1.0

164561B3

## LIGHT DISTRIBUTION



## CONE DIAGRAM

350mA 30°

h (m)	E0° (lx)	ø (m)
1	1460	0.54
2	360	1.09
3	160	1.63
4	90	2.17
5	60	2.71

## OPTICAL

### Honeycomb Louver

TYPE	Ø (MM)	ORDERCODE
CENO   PIRRO   BLIEK ROUND PETIT	29	9 0 0 5 1 1 3 1

## MOUNTING

### Plasterkit

TYPE	Ø · H (MM)	ORDERCODE
BLIEK PETIT TRIMLESS	ø73-29	9 0 0 1 7 2 1 0

## ELECTRICAL

### Driver

TYPE	L · W · H (MM)	VOLTAGE	ORDERCODE
6W   350mA	67-39-22	8.6-18V	9 0 2 1 3 3 0 3
10W   350mA   1-10V dim	101.5-51-29.5	14-28V	9 0 2 2 3 4 0 1
10W   350mA   phase-cut dim	102-38-21	12-28V	9 0 2 2 3 4 0 2
10W   350mA	115-41-25	13-26V	9 0 2 2 3 4 0 6
14W   350mA	145-33-21	2.5-42V	9 0 2 4 3 5 0 1
17W   350mA   10-49V   DALI	108-52-22	10-49V	9 0 2 4 3 6 0 1