



WEVER & DUCRÉ  
LIGHTING

# BOX mini 1.0 PAR16

258120G0

Project
Type
Notes
Quantity
Date

## GENERAL

Ceiling  
 Surface  
 Gold  
 IP20  
 Interior  
 375<sup>a</sup>, 410<sup>b</sup>, 415<sup>c</sup> lm

## LED

Lamp PAR16  
 PAR16  
 Socket GU10  
 max. 12 W  
 L70 / 50000 h

## OPTICAL

flood  
 Beam angle 48°


## PHYSICAL

Length 70 mm  
 Width 70 mm  
 Height 75 mm  
 0.16 kg


## ELECTRICAL

100 - 240 V  
 Total connected power 8.8<sup>c</sup>, 8.9<sup>b</sup>, 10<sup>a</sup>  
 W  
 PC1  
 Safety distance 0.3 m

- <sup>a</sup> LED 1800-2850K CRI 90 silver
- <sup>b</sup> LED 3000K CRI 80 white
- <sup>c</sup> LED 2700K CRI 80 white



## LIGHT DISTRIBUTION





**WEVER & DUCRÉ**  
LIGHTING

# BOX

## mini 1.0 PAR16

258120G0

### CONE DIAGRAM

LED 1800-2850K CRI ≥ 90 :

h (m)	E0° (lx)	Φ (m)
1	563	0.90
2	141	1.80
3	62	2.70
4	35	3.60
5	22	4.50

### LED LAMPS

#### PAR16 LED Lamp

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
2700K   >90 CRI   GU10	Jet Black	∅50 · 58	9 0 1 2 2 8 B 3
3000K   >90 CRI   GU10	Jet Black	∅50 · 58	9 0 1 2 2 8 B 5
2700K   >80 CRI   GU10	Signal White	∅50 · 58	9 0 1 2 2 8 W 2
2700K   >90 CRI   GU10	Signal White	∅50 · 58	9 0 1 2 2 8 W 3
3000K   >80 CRI   GU10	Signal White	∅50 · 58	9 0 1 2 2 8 W 4

#### PAR16 LED Lamp | Ambient

TYPE	Ø · H (MM)	ORDERCODE
1800-2850K   >90 CRI   GU10	∅50 · 58	9 0 1 2 2 9 S 9