



WEVER & DUCRÉ
LIGHTING

BOX WALL OUTDOOR 2.0

740148W2

Project
Type
Notes
Quantity
Date

GENERAL

Wall
 Surface
 Signal White
 IP65
 Exterior
 Total 400 lm
 9003^a

LED

2700 K
 CRI 80
 L90 / 50000 h
 3-step binning


PHYSICAL

Length 100 mm
 Width 100 mm
 Height 100 mm
 0.66 kg


ELECTRICAL

phase-cut dim
 220 - 240 V
 Total connected power 5.5 W
 PC1
 Safety distance 0.3 m

^a RAL Palette colors may deviate slightly due to production conditions.



IP65 $\pm 0,3$





WEVER & DUCRÉ
LIGHTING

BOX WALL OUTDOOR 2.0

740148W2

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.97	0.95	0.93	0.9	0.9
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.