



WEVER & DUCRÉ
LIGHTING

CENO SURFACE 4.1

176964Q3

Project	
Type	
Notes	
Quantity	
Date	

GENERAL

Ceiling , Surface
Tilt max 90°
Rotation 350°
Bronze
IP20
Interior
Output: 2040 lm
CIE flux code: 99 100 100 100 100

LED

2700 K
CRI ≥ 90
L70 / 55000h
2 SDCM

OPTICAL

Beam angle 31°

ELECTRICAL


phase-cut dim
220 - 240 V
Total connected power 29.6 W
Class 1

PHYSICAL

Diameter 34 mm
Height 55 mm
0.78 kg



Ceiling surface luminaire with 4 spotlights; made from die-cast aluminium; with rectangular base; surface Bronze; wet painted, matt smooth; inner ring black; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 2700 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; beam angle 31°; 220 - 240 V; 350° rotatable and 90° tiltable; degree of protection IP20; PC1; driver included; optional honeycomb louver available, to reduce glare; light source replaceable by an authorized professional; control gear replaceable by end-user;






WEVER & DUCRÉ
LIGHTING

CENO SURFACE 4.1

176964Q3

LIGHT DISTRIBUTION



CONE DIAGRAM

31°

h (m)	E0° (lx)	ø (m)
1	1460	0.56
2	370	1.12
3	160	1.68
4	90	2.23
5	60	2.79

OPTICAL

Honeycomb Louver

TYPE	Ø (MM)	ORDERCODE
CENO PIRRO BLIEK ROUND PETIT	29	90051131