



WEVER & DUCRÉ
LIGHTING

COSTA 1.0

865186YE9

Project

Type

Notes

Quantity

Date

GENERAL

Floor

Surface

White LLDPE + Colza Yellow

IP65

Exterior

130 lm

LED

4000 K

CRI 80

L90 / 50000 h

3-step binning

PHYSICAL

Diameter 235 mm

Height 350 mm

0.9 kg

ELECTRICAL

110 - 220 V

Total connected power 2.5 W


PC3



IP65  



LIGHT DISTRIBUTION





WEVER & DUCRÉ
LIGHTING

COSTA 1.0

865186YE9

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.95	0.93	0.91	0.9
LSF	1	1	1	1	1

MF	LMF × RSMF × LLMF × LSF	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

ROPE

Rope

TYPE	COLOUR	Ø·H (MM)	ORDERCODE
COSTA 1.0	Black	390·ø390-335	9 0 0 5 7 1 7 0
COSTA 1.0	Sand	ø390-335	9 0 0 5 7 1 7 1

POLE

POLE

TYPE	Ø·H (MM)	ORDERCODE
COSTA	450·ø350-1800	9 0 0 5 6 0 0 1