



WEVER & DUCRÉ  
LIGHTING

# DEEP ADJUST trimless 1.0 PAR16

112820G0

Project	.....
Type	.....
Notes	.....
Quantity	.....
Date	.....

## GENERAL

Ceiling  
 Recessed  
 Gold  
 IP20  
 Interior  
 450 lm

## LED

Lamp PAR16  
 PAR16  
 Socket GU10  
 max. 12 W  
 CRI 90

## OPTICAL

Beam angle 48°

## PHYSICAL


Diameter 96 mm  
 Height 106 mm  
 0.21 kg  
 Tilt min 35°  
 Tilt max 35°  
 Rotation 355°

## ELECTRICAL


100 - 240 V  
 LED Inset 6.5 W  
 Class 2  
 Safety distance 0.3 m

## CUTOUT


Diameter 105-110 mm  
 Recessed depth 110 mm



Round ceiling recessed downlight made from die-cast aluminium; adjustable; trimless; surface Gold; wet painted; matt smooth; to be combined with the plasterkit suitable for ceiling thickness; recessed depth 110 mm; lamp socket GU10; lamp type PAR16; max. 12W; 100 - 240 V; 355° rotatable and 35° tiltable; degree of protection IP20; PC2; lamp not included;



## LIGHT DISTRIBUTION



[112820G0] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.  
 © Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com



WEVER & DUCRÉ  
LIGHTING

# DEEP ADJUST trimless 1.0 PAR16

112820G0

## CONE DIAGRAM

LED 2700K CRI ≥ 80 White

h (m)	EO° (lx)	ø (m)
1	663	0.89
2	166	1.78
3	74	2.66
4	41	3.55
5	27	4.44

## MOUNTING

### PLASTERKIT

TYPE	Ø-H (MM)	ORDERCODE
DEEP ADJUST TRIMLESS	ø105-40	9 0 0 1 7 2 0 9

## LAMPS

### PAR16 LED Lamp

TYPE	COLOUR	Ø-H (MM)	ORDERCODE
2700K   >90 CRI   GU10	Black	ø50-58	9 0 1 2 2 8 B 3
3000K   >90 CRI   GU10	Black	ø50-58	9 0 1 2 2 8 B 5
2700K   >90 CRI   GU10	White	ø50-58	9 0 1 2 2 8 W 3
3000K   >90 CRI   GU10	White	ø50-58	9 0 1 2 2 8 W 5
2700K   >80 CRI   GU10	Silver	ø50-52	9 0 5 2 2 7 S 2
3000K   >80 CRI   GU10	Silver	ø50-52	9 0 5 2 2 7 S 4