



**WEVER & DUCRÉ**  
LIGHTING

# DEEP ASYM 1.0 PAR16

112420B0

Project	.....
Type	.....
Notes	.....
Quantity	.....
Date	.....

## GENERAL

Ceiling  
Recessed  
Jet Black  
IP20  
Interior  
375 lm  
RAL 9005<sup>a</sup>

## LED

Lamp PAR16  
PAR16  
Socket GU10  
max. 12 W  
CRI 90

## OPTICAL

Wide Flood

## PHYSICAL

Diameter 94 mm  
Height 110 mm  
0.23 kg  
Tilt min 35°  
Tilt max 35°  
Rotation 355°


## ELECTRICAL

100 - 240 V  
LED Inset 6.5 W  
Class 2  
Safety distance 0.3 m

## CUTOUT

Diameter 87-88 mm  
Min. ceiling thickness 4 mm  
Max. ceiling thickness 25 mm  
Recessed depth 115 mm


<sup>a</sup> Color may deviate slightly due to production conditions.



Round ceiling recessed downlight made from die-cast aluminium; adjustable; asymmetric light beam; surface Jet Black; powder coated; matt texture; RAL 9005; installation without tools using wire springs; suitable for ceiling thickness of 4-25 mm; recessed depth 115 mm; lamp socket GU10; lamp type PAR16; max. 12W; 100 - 240 V; 355° rotatable and 35° tiltable; degree of protection IP20; PC2; lamp not included;



## LIGHT DISTRIBUTION



[112420B0] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.  
© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com



WEVER & DUCRÉ  
LIGHTING

# DEEP ASYM 1.0 PAR16

112420B0

## OTHER

### Metal spring clip

TYPE	(MM)	ORDERCODE
MR16   LED   PAR16   max. 12W	59	9 0 0 1 9 7 0 0



### Spring clip

TYPE	COLOUR	(MM)	ORDERCODE
MR16   LED   PAR16   max. 12W	Black	59	9 0 0 1 9 8 B 0
MR16   LED   PAR16   max. 12W	Gold	59	9 0 0 1 9 8 G 0
MR16   LED   PAR16   max. 12W	Bronze	59	9 0 0 1 9 8 Q 0
MR16   LED   PAR16   max. 12W	Silver	59	9 0 0 1 9 8 S 0
MR16   LED   PAR16   max. 12W	White	59	9 0 0 1 9 8 W 0

## LAMPS

### PAR16 LED Lamp

TYPE	COLOUR	Ø·H (MM)	ORDERCODE
2700K   >90 CRI   GU10	Black	ø50·58	9 0 1 2 2 8 B 3
3000K   >90 CRI   GU10	Black	ø50·58	9 0 1 2 2 8 B 5
2700K   >90 CRI   GU10	White	ø50·58	9 0 1 2 2 8 W 3
3000K   >90 CRI   GU10	White	ø50·58	9 0 1 2 2 8 W 5
2700K   >80 CRI   GU10	Silver	ø50·52	9 0 5 2 2 7 S 2
3000K   >80 CRI   GU10	Silver	ø50·52	9 0 5 2 2 7 S 4