



WEVER & DUCRÉ  
LIGHTING

# DEEP point 1.0

185261M3

Project

Type

Notes

Quantity

Date

## GENERAL

Ceiling , Recessed

Champagne

IP20

Interior

Output: 390 lm

## LED

2700 K

2 SDCM

## OPTICAL

Flood , Beam angle 32°

## ELECTRICAL

excl. driver

18 V

LED Inset 4.0 W

Class 3

250 mA

## PHYSICAL

Diameter 45 mm

Height 42 mm

0.06 kg

wire springs

## CUTOUT

Diameter 40-41 mm

Min. ceiling thickness 4 mm

Max. ceiling thickness 25 mm

Recessed depth 68 mm





WEVER & DUCRÉ  
LIGHTING

# DEEP point 1.0

185261M3

## ELECTRICAL

### Driver

TYPE	L · W · H (MM)	VOLTAGE	ORDERCODE
6W   250mA	115 · 41 · 25	13-26V	9 0 2 2 6 2 0 1
7.2W   250mA   16-29V   phase-cut dim	122 · 41 · 23	16-29V	9 0 2 2 6 4 0 1
13W   250mA	144 · 33 · 21	2.5-52V	9 0 2 4 6 5 0 1
10W   250mA   6-40V   DALI	124 · 31 · 21	6-40V	9 0 2 4 9 4 0 2