

DEEPER 1.0 PAR16

152120B0

Project
Туре
Notes
Quantity
Date

CENEDAL			
GENERAL			
Ceiling			
Recessed			
Jet Black			
IP20			
Interior			
420 lm			
RAL 9005 a			
LED			
Lamp PAR16			
PAR16			
Socket GU10			
max. 12 W			
CRI 90			
OPTICAL			
Wide Flood			
Beam angle 48°			
PHYSICAL			
Diameter 84 mm			
Height 112 mm			
0.15 kg			
ELECTRICAL			
100 - 240 V			
LED Inset 6.5 W			
Class 2			
Safety distance 0.3 m			
ситоит			
Diameter 76-79 mm			
Min. ceiling thickness 4 mm			
Max. ceiling thickness 38 mm			
Recessed depth 115 mm			






Round ceiling recessed downlight made from die-cast aluminium; surface Jet Black; powder coated; matt texture; RAL 9005; installation without tools using wire springs; suitable for ceiling thickness of 4-38 mm; recessed depth 115 mm; lamp socket GU10; lamp type PAR16; max. 12W; 100 - 240 V; degree of protection IP20; PC2; lamp not included;



LIGHT DISTRIBUTION

a Color may deviate slightly due to production

conditions.





DEEPER 1.0 PAR16

152120B0

CONE DIAGRAM

wide flood 48°

h (m)	EO° (lx)	ø (m)
1	625	0.89
2	156	1.78
3	69	2.66
4	39	3.55
5	25	4.44

LAMPS

PAR16 LED Lamp

TYPE	COLOUR	Ø∙H (MM)	ORDERCODE
2700K >90 CRI GU10	Black	ø50·58	901228B3
3000K >90 CRI GU10	Black	ø50·58	901228B5
2700K >90 CRI GU10	White	Ø50·58	901228W3
3000K >90 CRI GU10	White	Ø50·58	901228W5
2700K >80 CRI GU10	Silver	Ø50·52	905227S2
3000K >80 CRI GU10	Silver	ø50·52	905227S4

June 18, 2022