



WEVER & DUCRÉ
LIGHTING

FIFTY FIFTY 1.0

756174D4

Project _____

Type _____

Notes _____

Quantity _____

Date _____

GENERAL

Floor _____

Surface _____

Dark Grey Texture _____

IP65 _____

Exterior _____

360 lm _____

LED

3000 K _____

CRI 80 _____

L95 / 50000 h _____

3-step binning _____

OPTICAL

Wide Flood _____

PHYSICAL

Length 130 mm _____

Width 30 mm _____

Height 130 mm _____

1.2 kg _____

ELECTRICAL

incl. PS | phase-cut dim _____

220 - 240 V _____


Total connected power 8 W _____

PC1 _____


Safety distance 0.3 m _____



IP65



LIGHT DISTRIBUTION



[756174D4] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BVBA apply.
© Wever & Ducré BVBA · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com



WEVER & DUCRÉ
LIGHTING

FIFTY FIFTY 1.0

756174D4

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.98	0.98	0.98	0.97
LSF	1	1	1	1	1

MF	LMF × RSMF × LLMF × LSF	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

BASE WITH CONCRETE FIXATION

BASE 1000

TYPE	L · W · H (MM)	ORDERCODE
with concrete ground fixation	130-30-870	9 1 0 0 7 0 D 0

BASE 300

TYPE	L · W · H (MM)	ORDERCODE
with concrete ground fixation	130-30-170	9 1 0 0 7 3 D 0

BASE 400

TYPE	L · W · H (MM)	ORDERCODE
with concrete ground fixation	130-30-270	9 1 0 0 7 4 D 0

BASE 600

TYPE	L · W · H (MM)	ORDERCODE
with concrete ground fixation	130-30-470	9 1 0 0 7 6 D 0

BASE 800

TYPE	L · W · H (MM)	ORDERCODE
with concrete ground fixation	130-30-670	9 1 0 0 7 8 D 0

BASE WITH FIXATION PLATE

BASE 1000

TYPE	L · W · H (MM)	ORDERCODE
with fixation plate	170-70-870	9 1 0 0 1 0 D 0

BASE 300

TYPE	L · W · H (MM)	ORDERCODE
with fixation plate	170-70-170	9 1 0 0 1 3 D 0



WEVER & DUCRÉ
LIGHTING

FIFTY FIFTY 1.0

756174D4

BASE 400

TYPE	L · W · H (MM)	ORDERCODE
with fixation plate	170-70-270	9 1 0 0 1 4 D 0

BASE 600

TYPE	L · W · H (MM)	ORDERCODE
with fixation plate	170-70-470	9 1 0 0 1 6 D 0

BASE 800

TYPE	L · W · H (MM)	ORDERCODE
with fixation plate	170-70-670	9 1 0 0 1 8 D 0