



WEVER & DUCRÉ
LIGHTING

FIFTY FIFTY 2.0

756274D4

Project

Type

Notes

Quantity

Date

GENERAL

Floor
Surface
Dark Grey Texture
IP65
Exterior
390 lm

LED

3000 K
CRI 80
L95 / 50000 h
3-step binning

OPTICAL

Wide Flood

PHYSICAL


Length 130 mm
Width 30 mm
Height 130 mm
0.98 kg

ELECTRICAL


incl. PS | phase-cut dim
220 - 240 V
Total connected power 8 W
PC1
Safety distance 0.3 m



IP65 0,3 m



LIGHT DISTRIBUTION



[756274D4] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BVBA apply.
© Wever & Ducré BVBA · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com



FIFTY FIFTY 2.0

756274D4

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.98	0.98	0.98	0.97
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

BASE WITH CONCRETE FIXATION

BASE 1000

TYPE	L · W · H (MM)	ORDERCODE
with concrete ground fixation	130-30-870	9 1 0 0 7 0 D 0

BASE 300

TYPE	L · W · H (MM)	ORDERCODE
with concrete ground fixation	130-30-170	9 1 0 0 7 3 D 0

BASE 400

TYPE	L · W · H (MM)	ORDERCODE
with concrete ground fixation	130-30-270	9 1 0 0 7 4 D 0

BASE 600

TYPE	L · W · H (MM)	ORDERCODE
with concrete ground fixation	130-30-470	9 1 0 0 7 6 D 0

BASE 800

TYPE	L · W · H (MM)	ORDERCODE
with concrete ground fixation	130-30-670	9 1 0 0 7 8 D 0

BASE WITH FIXATION PLATE

BASE 1000

TYPE	L · W · H (MM)	ORDERCODE
with fixation plate	170-70-870	9 1 0 0 1 0 D 0

BASE 300

TYPE	L · W · H (MM)	ORDERCODE
with fixation plate	170-70-170	9 1 0 0 1 3 D 0



WEVER & DUCRÉ
LIGHTING

FIFTY FIFTY 2.0

756274D4

BASE 400

TYPE	L · W · H (MM)	ORDERCODE
with fixation plate	170-70-270	9 1 0 0 1 4 D 0

BASE 600

TYPE	L · W · H (MM)	ORDERCODE
with fixation plate	170-70-470	9 1 0 0 1 6 D 0

BASE 800

TYPE	L · W · H (MM)	ORDERCODE
with fixation plate	170-70-670	9 1 0 0 1 8 D 0