### 7582A4A4

#### GENERAL

| Floor, Surface        |
|-----------------------|
| Anthracite Grey       |
| RAL 7016 <sup>a</sup> |
| IP65                  |
| Exterior              |
| Output: 600 lm        |

#### LED

3000 K 3 SDCM

## OPTICAL

Asymetric,

#### ELECTRICAL


| phase-cut dim                |
|------------------------------|
| 220 - 240 V                  |
| Total connected power 11.0 W |
| Class 1                      |

## PHYSICAL


| Diameter 80 mm |
|----------------|
| Height 28 mm   |
| 0.22 kg        |

<sup>a</sup> Color may deviate slightly due to production conditions.

| Project  |  |
|----------|--|
| Туре     |  |
| Notes    |  |
| Quantity |  |
| Date     |  |







7582A4A4

## MOUNTING

# **POLE 250**

| ТҮРЕ     | COLOUR          | Ø-H (MM) | ORDERCODE |
|----------|-----------------|----------|-----------|
| GATE 2.0 | Anthracite Grey | Ø80·250  | 910124A0  |
| GATE 2.0 | Bronze          | Ø80·250  | 910124Q0  |
| POLE 450 |                 |          |           |
| TYPE     | COLOUR          | Ø·H (MM) | ORDERCODE |
| GATE 2.0 | Anthracite Grey | ø80·450  | 910125A0  |
| GATE 2.0 |                 |          |           |

**POLE 650** 

| TYPE     | COLOUR          | Ø∙H (MM) | ORDERCODE |
|----------|-----------------|----------|-----------|
| GATE 2.0 | Anthracite Grey | Ø80-650  | 910126A0  |
| GATE 2.0 | Bronze          | Ø80.650  | 910126Q0  |