



WEVER & DUCRÉ  
LIGHTING

# GEO 1.0

767562A3

Project

Type

Notes

Quantity

Date

## GENERAL

Floor , Surface

Tilt max 135°

Anthracite Grey

RAL 7016 <sup>a</sup>

IP65

Exterior

Output: 250 lm

## LED

2700 K

3 SDCM

## OPTICAL

Flood , Beam angle 30°

## ELECTRICAL

excl. driver

24 V

LED Inset 4.0 W

Class 3



## PHYSICAL

Diameter 34 mm

Height 76 mm

0.29 kg

<sup>a</sup> Color may deviate slightly due to production conditions.





WEVER & DUCRÉ  
LIGHTING

# GEO 1.0

767562A3

## Driver

### Plug & Play Driver

TYPE	L · W · H (MM)	ORDERCODE
24W   IP67	118·35·26	9 0 0 1 8 0 1 4
60W   IP67	162,5·43·32	9 0 0 1 8 0 1 5

## Optional

### Plug & Play T-Connector

L · W · H (MM)	ORDERCODE
48·24·15	9 0 0 1 4 5 0 1

### Plug & Play Extension Cable

TYPE	LENGTH (MM)	ORDERCODE
2,5 m   IP67	2500	9 0 0 1 4 5 0 2
5 m   IP67	5000	9 0 0 1 4 5 0 3

### Plug & Play Straight Connector

TYPE	ORDERCODE
	9 0 0 1 4 5 0 4