



WEVER & DUCRÉ
LIGHTING

HEXO SUSPENDED 2.0 PAR16

227320P0

Project

Type

Notes

Quantity

Date

GENERAL

Ceiling

Suspended

Copper

IP20

Interior

445^a to 450^b lm

LED

Lamp PAR16

PAR16

Socket GU10

max. 12 W

CRI 80

OPTICAL

Beam angle 48°

PHYSICAL

Length 77 mm

Width 77 mm

Height 200 mm

0.58 kg

incl. 4.0 m suspension

ELECTRICAL

100 - 240 V

Total connected power 6.6^b to 6.7^a W

Class 1


Safety distance 0.3 m

^a LED 3000K CRI 80 white


^b LED 2700K CRI 80 white



Hexagonal ceiling suspended luminaire made from die-cast aluminium; surface Copper; wet painted; brushed; inclusive adjustable cable suspension max. 2500mm in Signal Black; lamp socket GU10; lamp type PAR16; max. 12W; 100 - 240 V; degree of protection IP20; PC1; lamp not included; ceiling base not included;



LIGHT DISTRIBUTION



[227320P0] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.
© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com



WEVER & DUCRÉ
LIGHTING

HEXO SUSPENDED 2.0 PAR16

227320P0

CONE DIAGRAM

LED 2700K CRI ≥ 80 White

h (m)	EO° (lx)	ø (m)
1	632	0.89
2	158	1.78
3	70	2.67
4	40	3.56
5	25	4.45

LAMPS

PAR16 LED Lamp

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
2700K >90 CRI GU10	Black	ø50-58	9 0 1 2 2 8 B 3
3000K >90 CRI GU10	Black	ø50-58	9 0 1 2 2 8 B 5
2700K >90 CRI GU10	White	ø50-58	9 0 1 2 2 8 W 3
3000K >90 CRI GU10	White	ø50-58	9 0 1 2 2 8 W 5
2700K >80 CRI GU10	Silver	ø50-52	9 0 5 2 2 7 S 2
3000K >80 CRI GU10	Silver	ø50-52	9 0 5 2 2 7 S 4

OPTIONAL

Cable Wall-Ceiling Bracket

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
for cable 4.25-5.5mm diameter	White	ø16-30	9 0 0 1 9 1 9 7
for cable 4.25-5.5mm diameter	Black	ø16-30	9 0 0 1 9 1 9 8

Hook

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
standard multi suspension hook	Black	ø3-83	9 0 0 5 2 0 2 4
standard multi suspension hook	White	ø3-83	9 0 0 5 2 0 2 5
optional multi suspension hook	Black	ø5-90	9 0 0 5 2 0 6 5
optional multi suspension hook	White	ø5-90	9 0 0 5 2 0 6 6

WALL BASE

WALL BASE

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
for 1 luminaire	White	ø82-32	9 0 0 1 9 1 9 5
for 1 luminaire	Black	ø82-32	9 0 0 1 9 1 9 6

Cable Wall-Ceiling Bracket

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
for cable 4.25-5.5mm diameter	White	ø16-30	9 0 0 1 9 1 9 7
for cable 4.25-5.5mm diameter	Black	ø16-30	9 0 0 1 9 1 9 8

[227320P0] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.
© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com

June 18, 2022



WEVER & DUCRÉ
LIGHTING

HEXO SUSPENDED 2.0 PAR16

227320P0

SINGLE SUSPENSION

Invisible ceiling base

COLOUR	L · W (MM)	ORDERCODE
Black	140-66	9 0 0 1 5 1 9 5
White	140-66	9 0 0 1 5 1 9 6



Single base

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
ceiling base round	Black	∅84-29	9 0 0 5 2 0 2 1
ceiling base round	White	∅84-29	9 0 0 5 2 0 2 2

Semi recessed base

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
for shades without steel wire only	White	∅84-72	9 0 0 5 2 0 2 6
for shades without steel wire only	Black	∅84-72	9 0 0 5 2 0 2 7

MULTI SUSPENSION

Multiple base round

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
up to max. 4 luminaires	White	∅123-44	9 0 0 5 2 0 0 5
up to max. 4 luminaires	Black	∅123-44	9 0 0 5 2 0 0 6
up to max. 8 luminaires	White	∅123-44	9 0 0 5 2 0 3 1
up to max. 8 luminaires	Black	∅123-44	9 0 0 5 2 0 3 2

Multiple base linear

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
up to max. 2 luminaires	White	600-30-45	9 0 0 5 2 0 0 7
up to max. 2 luminaires	Black	600-30-45	9 0 0 5 2 0 0 8
up to max. 3 luminaires	White	900-30-45	9 0 0 5 2 0 0 9
up to max. 3 luminaires	Black	900-30-45	9 0 0 5 2 0 1 0
up to max. 4 luminaires	White	1200-30-45	9 0 0 5 2 0 1 1
up to max. 4 luminaires	Black	1200-30-45	9 0 0 5 2 0 1 2
up to max. 5 luminaires	White	1500-30-45	9 0 0 5 2 0 1 3
up to max. 5 luminaires	Black	1500-30-45	9 0 0 5 2 0 1 4

[227320P0] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.
© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com