


**FEATURES**

- High end aluminum heatsink with a unique elegant design
- PCB with a high power Lumileds Powerleds in 2700K, 3000K and 4000K
- Illuxtron patented optical lens system that makes pin-hole light possible
- Anti glare cap that ensures no stray light. The total light opening is only 8mm!



**COLOURS**

Available colours:



Nr	Housing	Ring
	RAL 9016	
XX=61	Matt white	Gold
XX=63	Matt white	Silver
XX=62	Matt white	Black
XX=65	Matt white	White



Nr	Housing	Ring
	RAL 9005	
XX=71	Matt black	Gold
XX=74	Matt black	Silver
XX=72	Matt black	Black
XX=76	Matt black	White



# Pointer Spot WL LV


Adjustable

## SPECIFICATIONS

<b>Beam angle (FWHM)</b>	35° (45° FWTM) / 60° (80° FWTM)
<b>Fixture material</b>	Die cast aluminium
<b>Environment</b>	Indoor
<b>IK rate</b>	IK10
<b>Operating temperature (Ta)</b>	-20°C / +45°C <sup>1</sup>
<b>Safety marks</b>	EN60598 / EN62031 / EN62471
<b>EMC compliance</b>	EN55015
<b>Colour consistency (SDCM)</b>	MacAdam step 3
<b>Warranty</b>	7 years * (within the European Union and the countries of the Free Trade Association for products delivered after 1 May 2015)
<b>Energy class</b>	This product contains a light source of energy efficiency class F (2700K/3000K) and class E (4000K)

This luminaire contains built-in LED lamps. There are no exchangeable parts inside the luminaire. EU 874/2012

<sup>1</sup> In applications with a flat roof (fi. car showrooms) the temperatures may exceed 45°C. Please ask our sales office for a special driver.



IP20

**POINTER SPOT WL LV** (dimnable - incl. individual power supply)

**220-240V**

**ITEM SPECIFICATIONS (PART A)**

Description	Item code	Input	W	Lm	Lm/W	CRI (typ.)	UGR	Pf	Ripple	Inrush current	B-16A Fuse
Pointer Spot WL LV 35° 175 Lm 2700K No dim	0W2703XXLU02	220-240V	3,3	175	53	82	6.1	0.95	<3%	5A 50µS	50 pcs
Pointer Spot WL LV 35° 200 Lm 3000K No dim	0W2703XXLV02	220-240V	3,3	200	61	82	6.6	0.95	<3%	5A 50µS	50 pcs
Pointer Spot WL LV 35° 225 Lm 4000K No dim	0W2703XXLW02	220-240V	3,3	225	68	82	7.0	0.95	<3%	5A 50µS	50 pcs
Pointer Spot WL LV 60° 225 Lm 2700K No dim	0W2703XXLX02	220-240V	3,3	225	68	82	16.9	0.95	<3%	5A 50µS	50 pcs
Pointer Spot WL LV 60° 250 Lm 3000K No dim	0W2703XXLY02	220-240V	3,3	250	76	82	17.3	0.95	<3%	5A 50µS	50 pcs
Pointer Spot WL LV 60° 275 Lm 4000K No dim	0W2703XXLZ02	220-240V	3,3	275	83	82	17.6	0.95	<3%	5A 50µS	50 pcs

**ITEM SPECIFICATIONS (PART B)**

Description	Safety class	Energy class	Weight	Dimensions single carton	Quantity per carton	Expected lifespan B10 reported (25°C)		
						L70B10	L80B10	L90B10
Pointer Spot WL LV 2700K	I	F	276 gr	105x105x61 mm	42 pcs	>60.000 hrs	>60.000 hrs	>60.000 hrs
Pointer Spot WL LV 3000K	I	F	276 gr	105x105x61 mm	42 pcs	>60.000 hrs	>60.000 hrs	>60.000 hrs
Pointer Spot WL LV 4000K	I	E	276 gr	105x105x61 mm	42 pcs	>60.000 hrs	>60.000 hrs	>60.000 hrs

All values are measured at 230V (+/- 7%)

**DIMENSIONS**

