

FEATURES

- IP65
- High CRI LED optimized towards TM30
- ENEC approved drivers



COLOURS

Available colours:



Nr	Housing	Inside ring
	RAL 9016	
XX=65	Matt white	White
XX=62	Matt white	Black



Nr	Housing	Inside ring
	RAL 9005	
XX=76	Matt black	White
XX=72	Matt black	Black

Strada 68 IP65 LV(-HE)

Fixed


SPECIFICATIONS

Beam angle (FWHM)	24° / 60° / 80°
Fixture material	Housing: Die cast aluminium / Reflector glass: Polycarbonate
Environment	Indoor
IK rate	IK03
Operating temperature (Ta)	-20°C / +45°C ¹
Safety marks	EN60598 / EN62031 / EN62471
EMC compliance	EN55015
Colour consistency (SDCM)	MacAdam step 3
Warranty	7 years * (within the European Union and the countries of the Free Trade Association for products delivered after 1 May 2015)
Safety class	II
Energy class	These products contains a light source of energy efficiency class G (1800-3000K) / F (2700K/3000K) / E (4000K)
Energy class	These products contains a light source of energy efficiency class: CRI97 - G (1800-3000K) / F (2700K/3000K) / E (4000K) & CRI82 - E (2700K/3000K) / D (4000K)

This luminaire contains built-in LED lamps. There are no exchangeable parts inside the luminaire. EU 874/2012

¹ In applications with a flat roof (f.i. car showrooms) the temperatures may exceed 45°C. Please ask our sales office for a special driver.

Ask our sales department about the possibilities for:
- High CRI LED options



IP65

CRI82 VARIATIONS

Strada 68 IP65 LV-HE 2700K CRI82 1650LM	page 3
Strada 68 IP65 LV-HE 3000K CRI82 1725LM	page 4
Strada 68 IP65 LV-HE 4000K CRI82 1750LM	page 5

CRI97 VARIATIONS

Strada 68 IP65 LV 2700K CRI97 1150LM	page 6
Strada 68 IP65 LV 3000K CRI97 1250LM	page 7
Strada 68 IP65 LV 4000K CRI97 1350LM	page 8
Strada 68 IP65 LV 1800-3000K CRI97 1250LM	page 9


CRI82 CHOOSE YOUR LV LUMEN OUTPUT

	mA	W	Lumen Output			Lumen / Watt			UGR			Driver types	
			2700K	3000K	4000K	2700K	3000K	4000K	3000K			No dim	Dali
									24°	60°	80°		
Special request	125	4,5	625	650	675	140	145	151				127570	x
Special request	150	5,4	750	775	800	139	144	149				CC21W150-500	x
Special request	200	7,2	1000	1025	1050	139	142	145				CC21W150-500	x
Special request	250	9,1	1225	1250	1275	135	138	140				CC21W150-500	127576
Special request	300	11,0	1450	1500	1525	132	137	139				CC21W150-500	127576
Standard	350	12,9	1650	1725	1750	128	134	136	24,2	25,1	29,6	CC21W150-500	127576

CRI97 CHOOSE YOUR LV LUMEN OUTPUT

	mA	W	Lumen Output			Lumen / Watt			UGR			Driver types	
			2700K	3000K	4000K	2700K	3000K	4000K	3000K			No dim	Dali
									24°	60°	80°		
Special request	125	5,0	475	500	525	95	100	105				127570	x
Special request	150	6,1	550	575	625	91	95	103				CC21W150-500	x
Special request	200	8,1	700	750	825	86	93	102				CC21W150-500	x
Special request	250	9,8	850	900	1000	87	92	102				CC21W150-500	127576
Special request	300	12,0	1050	1100	1200	88	92	100				CC21W150-500	127576
Standard	350	13,8	1150	1250	1350	83	91	98	23,1	24,0	28,4	CC21W150-500	127576

DIMENSIONS




HOLE SIZE



Using WS springs: Ø 68 mm.
Thickness ceiling 1-54 mm
& recess depth 60 mm . .


DRIVER CONNECTION



STRADA 68 IP65 LV-HE

2700K CRI82 1650LM

Downlight incl. PSU



ITEM SPECIFICATIONS (PART A)

Description	Item code WS	Extra	Input	W	Lm	Lm/W	CRI (typ.)
Strada 68 IP65 LV-HE 2700K 1650Lm CRI82 24° No dim	85SN03XX9K02	incl. PSU	220-240V	12,9	1650	128	82
Strada 68 IP65 LV-HE 2700K 1650Lm CRI82 24° Dali	85SN03XX9B02	incl. PSU	220-240V	12,9	1650	128	82
Strada 68 IP65 LV-HE 2700K 1650Lm CRI82 60° No dim	85SN03XX9L02	incl. PSU	220-240V	12,9	1650	128	82
Strada 68 IP65 LV-HE 2700K 1650Lm CRI82 60° Dali	85SN03XX9E02	incl. PSU	220-240V	12,9	1650	128	82
Strada 68 IP65 LV-HE 2700K 1650Lm CRI82 80° No dim	85SN03XX9M02	incl. PSU	220-240V	12,9	1650	128	82
Strada 68 IP65 LV-HE 2700K 1650Lm CRI82 80° Dali	85SN03XX9H02	incl. PSU	220-240V	12,9	1650	128	82

ITEM SPECIFICATIONS (PART B)

Description	R9	Rf	Rg	R15	UGR	Pf	Ripple	Inrush	B16A
Strada 68 IP65 LV-HE 2700K 1650Lm CRI82 24° No dim	87	83	95	82	24.1	0.93	<3%	21A 180µS	50 pcs
Strada 68 IP65 LV-HE 2700K 1650Lm CRI82 24° Dali	87	83	95	82	24.1	0.95	<5%	5A 50µS	50 pcs
Strada 68 IP65 LV-HE 2700K 1650Lm CRI82 60° No dim	87	83	95	82	24.9	0.93	<3%	21A 180µS	50 pcs
Strada 68 IP65 LV-HE 2700K 1650Lm CRI82 60° Dali	87	83	95	82	24.9	0.95	<5%	5A 50µS	50 pcs
Strada 68 IP65 LV-HE 2700K 1650Lm CRI82 80° No dim	87	83	95	82	29.4	0.93	<3%	21A 180µS	50 pcs
Strada 68 IP65 LV-HE 2700K 1650Lm CRI82 80° Dali	87	83	95	82	29.4	0.95	<5%	5A 50µS	50 pcs

ITEM SPECIFICATIONS (PART C)


Description	Safety class	Energy class	Weight	Dimensions single carton	Quantity per carton	Expected lifespan B10 reported (25°C)		
						L70B10	L80B10	L90B10
Strada 68 IP65 LV-HE 2700K 1650Lm CRI82	II	E	552 gr	160x107x100 mm	18 pcs	>60.500 hrs	>60.500 hrs	>60.500 hrs

All values are measured at 230V (+/- 7%)

STRADA 68 IP65 LV-HE

3000K CRI82 1725LM

Downlight incl. PSU



ITEM SPECIFICATIONS (PART A)

Description	Item code WS	Extra	Input	W	Lm	Lm/W	CRI (typ.)
Strada 68 IP65 LV-HE 3000K 1725Lm CRI82 24° No dim	85SP03XX9K02	incl. PSU	220-240V	12,9	1725	134	82
Strada 68 IP65 LV-HE 3000K 1725Lm CRI82 24° Dali	85SP03XX9B02	incl. PSU	220-240V	12,9	1725	134	82
Strada 68 IP65 LV-HE 3000K 1725Lm CRI82 60° No dim	85SP03XX9L02	incl. PSU	220-240V	12,9	1725	134	82
Strada 68 IP65 LV-HE 3000K 1725Lm CRI82 60° Dali	85SP03XX9E02	incl. PSU	220-240V	12,9	1725	134	82
Strada 68 IP65 LV-HE 3000K 1725Lm CRI82 80° No dim	85SP03XX9M02	incl. PSU	220-240V	12,9	1725	134	82
Strada 68 IP65 LV-HE 3000K 1725Lm CRI82 80° Dali	85SP03XX9H02	incl. PSU	220-240V	12,9	1725	134	82

ITEM SPECIFICATIONS (PART B)

Description	R9	Rf	Rg	R15	UGR	Pf	Ripple	Inrush	B16A
Strada 68 IP65 LV-HE 3000K 1725Lm CRI82 24° No dim	89	84	97	80	24.2	0.93	<3%	21A 180µS	50 pcs
Strada 68 IP65 LV-HE 3000K 1725Lm CRI82 24° Dali	89	84	97	80	24.2	0.95	<5%	5A 50µS	50 pcs
Strada 68 IP65 LV-HE 3000K 1725Lm CRI82 60° No dim	89	84	97	80	25.1	0.93	<3%	21A 180µS	50 pcs
Strada 68 IP65 LV-HE 3000K 1725Lm CRI82 60° Dali	89	84	97	80	25.1	0.95	<5%	5A 50µS	50 pcs
Strada 68 IP65 LV-HE 3000K 1725Lm CRI82 80° No dim	89	84	97	80	29.6	0.93	<3%	21A 180µS	50 pcs
Strada 68 IP65 LV-HE 3000K 1725Lm CRI82 80° Dali	89	84	97	80	29.6	0.95	<5%	5A 50µS	50 pcs

ITEM SPECIFICATIONS (PART C)


Description	Safety class	Energy class	Weight	Dimensions single carton	Quantity per carton	Expected lifespan B10 reported (25°C)		
						L70B10	L80B10	L90B10
Strada 68 IP65 LV-HE 3000K 1725Lm CRI82	II	E	552 gr	160x107x100 mm	18 pcs	>60.500 hrs	>60.500 hrs	>60.500 hrs

All values are measured at 230V (+/- 7%)

STRADA 68 IP65 LV-HE

4000K CRI82 1750LM

Downlight incl. PSU



ITEM SPECIFICATIONS (PART A)

Description	Item code WS	Extra	Input	W	Lm	Lm/W	CRI (typ.)
Strada 68 IP65 LV-HE 4000K 1750Lm CRI82 24° No dim	85SQ03XX9K02	incl. PSU	220-240V	12,9	1750	136	82
Strada 68 IP65 LV-HE 4000K 1750Lm CRI82 24° Dali	85SQ03XX9B02	incl. PSU	220-240V	12,9	1750	136	82
Strada 68 IP65 LV-HE 4000K 1750Lm CRI82 60° No dim	85SQ03XX9L02	incl. PSU	220-240V	12,9	1750	136	82
Strada 68 IP65 LV-HE 4000K 1750Lm CRI82 60° Dali	85SQ03XX9E02	incl. PSU	220-240V	12,9	1750	136	82
Strada 68 IP65 LV-HE 4000K 1750Lm CRI82 80° No dim	85SQ03XX9M02	incl. PSU	220-240V	12,9	1750	136	82
Strada 68 IP65 LV-HE 4000K 1750Lm CRI82 80° Dali	85SQ03XX9H02	incl. PSU	220-240V	12,9	1750	136	82

ITEM SPECIFICATIONS (PART B)

Description	R9	Rf	Rg	R15	UGR	Pf	Ripple	Inrush	B16A
Strada 68 IP65 LV-HE 4000K 1750Lm CRI82 24° No dim	89	84	97	79	24.3	0.93	<3%	21A 180µS	50 pcs
Strada 68 IP65 LV-HE 4000K 1750Lm CRI82 24° Dali	89	84	97	79	24.3	0.95	<5%	5A 50µS	50 pcs
Strada 68 IP65 LV-HE 4000K 1750Lm CRI82 60° No dim	89	84	97	79	25.2	0.93	<3%	21A 180µS	50 pcs
Strada 68 IP65 LV-HE 4000K 1750Lm CRI82 60° Dali	89	84	97	79	25.2	0.95	<5%	5A 50µS	50 pcs
Strada 68 IP65 LV-HE 4000K 1750Lm CRI82 80° No dim	89	84	97	79	29.6	0.93	<3%	21A 180µS	50 pcs
Strada 68 IP65 LV-HE 4000K 1750Lm CRI82 80° Dali	89	84	97	79	29.6	0.95	<5%	5A 50µS	50 pcs

ITEM SPECIFICATIONS (PART C)


Description	Safety class	Energy class	Weight	Dimensions single carton	Quantity per carton	Expected lifespan B10 reported (25°C)		
						L70B10	L80B10	L90B10
Strada 68 IP65 LV-HE 4000K 1750Lm CRI82	II	D	552 gr	160x107x100 mm	18 pcs	>60.500 hrs	>60.500 hrs	>60.500 hrs

All values are measured at 230V (+/- 7%)

STRADA 68 IP65 LV

2700K CRI97 1150LM

Downlight incl. PSU



ITEM SPECIFICATIONS (PART A)

Description	Item code WS	Extra	Input	W	Lm	Lm/W	CRI (typ.)
Strada 68 IP65 LV 2700K 1150Lm CRI97 24° No dim	85RN03XX9K02	incl. PSU	220-240V	13,8	1150	83	97
Strada 68 IP65 LV 2700K 1150Lm CRI97 24° Dali	85RN03XX9B02	incl. PSU	220-240V	13,8	1150	83	97
Strada 68 IP65 LV 2700K 1150Lm CRI97 60° No dim	85RN03XX9L02	incl. PSU	220-240V	13,8	1150	83	97
Strada 68 IP65 LV 2700K 1150Lm CRI97 60° Dali	85RN03XX9E02	incl. PSU	220-240V	13,8	1150	83	97
Strada 68 IP65 LV 2700K 1150Lm CRI97 80° No dim	85RN03XX9M02	incl. PSU	220-240V	13,8	1150	83	97
Strada 68 IP65 LV 2700K 1150Lm CRI97 80° Dali	85RN03XX9H02	incl. PSU	220-240V	13,8	1150	83	97

ITEM SPECIFICATIONS (PART B)

Description	R9	Rf	Rg	R15	UGR	Pf	Ripple	Inrush	B16A
Strada 68 IP65 LV 2700K 1150Lm CRI97 24° No dim	93	96	103	99	22.8	0.93	<3%	21A 180µS	50 pcs
Strada 68 IP65 LV 2700K 1150Lm CRI97 24° Dali	93	96	103	99	22.8	0.95	<5%	5A 50µS	50 pcs
Strada 68 IP65 LV 2700K 1150Lm CRI97 60° No dim	93	96	103	99	23.7	0.93	<3%	21A 180µS	50 pcs
Strada 68 IP65 LV 2700K 1150Lm CRI97 60° Dali	93	96	103	99	23.7	0.95	<5%	5A 50µS	50 pcs
Strada 68 IP65 LV 2700K 1150Lm CRI97 80° No dim	93	96	103	99	28.1	0.93	<3%	21A 180µS	50 pcs
Strada 68 IP65 LV 2700K 1150Lm CRI97 80° Dali	93	96	103	99	28.1	0.95	<5%	5A 50µS	50 pcs

ITEM SPECIFICATIONS (PART C)


Description	Safety class	Energy class	Weight	Dimensions single carton	Quantity per carton	Expected lifespan B10 reported (25°C)		
						L70B10	L80B10	L90B10
Strada 68 IP65 LV 2700K 1150Lm CRI97	II	F	552 gr	160x107x100 mm	18 pcs	>60.500 hrs	>60.500 hrs	>60.500 hrs

All values are measured at 230V (+/- 7%)

STRADA 68 IP65 LV

3000K CRI97 1250LM

Downlight incl. PSU



ITEM SPECIFICATIONS (PART A)

Description	Item code WS	Extra	Input	W	Lm	Lm/W	CRI (typ.)
Strada 68 IP65 LV 3000K 1250Lm CRI97 24° No dim	85RP03XX9K02	incl. PSU	220-240V	13,8	1250	91	97
Strada 68 IP65 LV 3000K 1250Lm CRI97 24° Dali	85RP03XX9B02	incl. PSU	220-240V	13,8	1250	91	97
Strada 68 IP65 LV 3000K 1250Lm CRI97 60° No dim	85RP03XX9L02	incl. PSU	220-240V	13,8	1250	91	97
Strada 68 IP65 LV 3000K 1250Lm CRI97 60° Dali	85RP03XX9E02	incl. PSU	220-240V	13,8	1250	91	97
Strada 68 IP65 LV 3000K 1250Lm CRI97 80° No dim	85RP03XX9M02	incl. PSU	220-240V	13,8	1250	91	97
Strada 68 IP65 LV 3000K 1250Lm CRI97 80° Dali	85RP03XX9H02	incl. PSU	220-240V	13,8	1250	91	97

ITEM SPECIFICATIONS (PART B)

Description	R9	Rf	Rg	R15	UGR	Pf	Ripple	Inrush	B16A
Strada 68 IP65 LV 3000K 1250Lm CRI97 24° No dim	96	95	103	100	23.1	0.93	<3%	21A 180µS	50 pcs
Strada 68 IP65 LV 3000K 1250Lm CRI97 24° Dali	96	95	103	100	23.1	0.95	<5%	5A 50µS	50 pcs
Strada 68 IP65 LV 3000K 1250Lm CRI97 60° No dim	96	95	103	100	24.0	0.93	<3%	21A 180µS	50 pcs
Strada 68 IP65 LV 3000K 1250Lm CRI97 60° Dali	96	95	103	100	24.0	0.95	<5%	5A 50µS	50 pcs
Strada 68 IP65 LV 3000K 1250Lm CRI97 80° No dim	96	95	103	100	28.4	0.93	<3%	21A 180µS	50 pcs
Strada 68 IP65 LV 3000K 1250Lm CRI97 80° Dali	96	95	103	100	28.4	0.95	<5%	5A 50µS	50 pcs

ITEM SPECIFICATIONS (PART C)


Description	Safety class	Energy class	Weight	Dimensions single carton	Quantity per carton	Expected lifespan B10 reported (25°C)		
						L70B10	L80B10	L90B10
Strada 68 IP65 LV 3000K 1250Lm CRI97	II	F	552 gr	160x107x100 mm	18 pcs	>60.500 hrs	>60.500 hrs	>60.500 hrs

All values are measured at 230V (+/- 7%)

STRADA 68 IP65 LV

4000K CRI97 1350LM

Downlight incl. PSU



ITEM SPECIFICATIONS (PART A)

Description	Item code WS	Extra	Input	W	Lm	Lm/W	CRI (typ.)
Strada 68 IP65 LV 4000K 1350Lm CRI97 24° No dim	85RQ03XX9K02	incl. PSU	220-240V	13,8	1350	98	97
Strada 68 IP65 LV 4000K 1350Lm CRI97 24° Dali	85RQ03XX9B02	incl. PSU	220-240V	13,8	1350	98	97
Strada 68 IP65 LV 4000K 1350Lm CRI97 60° No dim	85RQ03XX9L02	incl. PSU	220-240V	13,8	1350	98	97
Strada 68 IP65 LV 4000K 1350Lm CRI97 60° Dali	85RQ03XX9E02	incl. PSU	220-240V	13,8	1350	98	97
Strada 68 IP65 LV 4000K 1350Lm CRI97 80° No dim	85RQ03XX9M02	incl. PSU	220-240V	13,8	1350	98	97
Strada 68 IP65 LV 4000K 1350Lm CRI97 80° Dali	85RQ03XX9H02	incl. PSU	220-240V	13,8	1350	98	97

ITEM SPECIFICATIONS (PART B)

Description	R9	Rf	Rg	R15	UGR	Pf	Ripple	Inrush	B16A
Strada 68 IP65 LV 4000K 1350Lm CRI97 24° No dim	96	95	103	100	23.4	0.93	<3%	21A 180µS	50 pcs
Strada 68 IP65 LV 4000K 1350Lm CRI97 24° Dali	96	95	103	100	23.4	0.95	<5%	5A 50µS	50 pcs
Strada 68 IP65 LV 4000K 1350Lm CRI97 60° No dim	96	95	103	100	24.2	0.93	<3%	21A 180µS	50 pcs
Strada 68 IP65 LV 4000K 1350Lm CRI97 60° Dali	96	95	103	100	24.2	0.95	<5%	5A 50µS	50 pcs
Strada 68 IP65 LV 4000K 1350Lm CRI97 80° No dim	96	95	103	100	28.7	0.93	<3%	21A 180µS	50 pcs
Strada 68 IP65 LV 4000K 1350Lm CRI97 80° Dali	96	95	103	100	28.7	0.95	<5%	5A 50µS	50 pcs

ITEM SPECIFICATIONS (PART C)


Description	Safety class	Energy class	Weight	Dimensions single carton	Quantity per carton	Expected lifespan B10 reported (25°C)		
						L70B10	L80B10	L90B10
Strada 68 IP65 LV 4000K 1350Lm CRI97	II	E	552 gr	160x107x100 mm	18 pcs	>60.500 hrs	>60.500 hrs	>60.500 hrs

All values are measured at 230V (+/- 7%)

STRADA 68 IP65 LV

1800-3000K CRI97 1250LM

Downlight incl. PSU



ITEM SPECIFICATIONS (PART A)

Description	24°		60°		80°	
	Item code	UGR	Item code	UGR	Item code	UGR
	WS		WS		WS	
Strada 68 IP65 LV 1800-3000K 1250Lm CRI97 Dali	85RR03XX9B02	23.1	85RR03XX9E02	24.0	85RR03XX9H02	28.4

ITEM SPECIFICATIONS (PART B)

Description	CCT	W	Lm	Lm/W	CRI (typ.)	R9	Rf	Rg	mA	Pf	Ripple	Inrush	B16A	
Strada 68 IP65 LV 1800-3000K 1250Lm CRI97 Dali	100%	3000	13,8	1250	91	97	93	95	102	350	0.95	<5%	200mA*s	106 pcs
	50%	2500	6,9	625	90	94	90	95	105					
	25%	2200	3,4	300	88	93	94	93	105					
	10%	1800	1,4	125	89	92	97	86	110					

ITEM SPECIFICATIONS (PART C)

Description	Safety class	Energy class	Weight	Dimensions single carton	Quantity per carton	Expected lifespan B10 reported (25°C)		
						L70B10	L80B10	L90B10
Strada 68 IP65 LV 1800-3000K 1250Lm CRI97	II	G	552 gr	160x107x100 mm	18 pcs	>60.500 hrs	>60.500 hrs	>60.500 hrs

All values are measured at 230V (+/- 7%)

NEW STANDARDS REQUIRE NEW LEDS

TM-30 (new color norm): The Illuminating Engineering Society (IES) has published a new Technical Memorandum – TM-30-15 entitled “IES Method for Evaluating Light Source Color Rendition” – that promises to supplant CRI as a color metric. TM-30 relies on separate fidelity and gamut metrics, as well as a set of color samples that is more representative of real-world objects, as opposed to the pastel samples that were primarily used for the baseline CRI metric that was sometimes called Ra. The new color metric is intended to fairly and accurately characterize both LED-based solid-state lighting (SSL) and legacy sources.



Desaturated

CRI = 82 / R_g = 94






Red-Enhanced

CRI = 97 / R_g = 103

HIGH CRI LED OPTIONS




	CCT	CRI	R9	RF	RG	DOWNLIGHTS SMALL			DOWNLIGHTS LARGE		DOWNLIGHTS LARGE		BRAND	ITEM CODE
						MA	LM	LM/W	MA	LM	MA	LM		
CRI82	2700K	82	5	83	94	350	1650	128	700	3400	1200	5300	Bridgelux ksf	51-4087-27
CRI82	3000K	82	7	86	95	350	1725	134	700	3575	1200	5550	Bridgelux ksf	51-4087-30
CRI82	4000K	82	18	84	96	350	1750	136	700	3650	1200	5800	Bridgelux ksf	51-4087-40
CRI90	2700K	92	67	88	104	350	1550	118	700	3150	1200	4700	Bridgelux ksf	51-4088-27
CRI90	3000K	92	67	92	99	350	1600	122	700	3250	1200	4850	Bridgelux ksf	51-4088-30
CRI90	4000K	92	78	92	100	350	1625	124	700	3300	1200	4925	Bridgelux ksf	51-4088-40
CRI97	2700K	97	93	96	103	350	1150	83	800	2300	1400	3425	Lumileds	50-3031-27
CRI97	3000K	97	96	95	103	350	1250	91	800	2500	1400	3750	Lumileds	50-3031-30
CRI97	4000K	97	96	95	103	350	1350	98	800	2700	1400	4050	Lumileds	50-3031-40

2700K






CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS
2700K	96.9	92.7	96.0	102.6	94.6

3000K



CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS
3000 K	97.0	96.2	95.0	103.3	95.1

4000K



CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS
4000K	96.6	98.5	88.3	96.2	93.5