



WEVER & DUCRÉ
LIGHTING

LECA 1.0

188161B3

Project

Type

Notes

Quantity

Date

GENERAL

Ceiling, Recessed

Tilt max 90°

Rotation 350°

Black Matt

IP20

Interior

Output: 510 lm

LED

2700 K

2 SDCM

OPTICAL

Flood, Beam angle 31°

ELECTRICAL

excl. driver

18 V

LED Inset 6.0 W

Class 3

350 mA

PHYSICAL

Diameter 60 mm

Height 73 mm

0.32 kg

wire springs



CUTOUT

Diameter 40-41 mm

Min. ceiling thickness 4 mm

Max. ceiling thickness 26 mm

Recessed depth 68 mm





WEVER & DUCRÉ
LIGHTING

LECA 1.0

188161B3

OPTICAL

Honeycomb Louver

TYPE	Ø (MM)	ORDERCODE
BLIEK PETIT CENO LECA PIRRO	29	9 0 0 5 1 1 3 1

ELECTRICAL

Driver

TYPE	L · W · H (MM)	VOLTAGE	ORDERCODE
6W 350mA	67-39-22	8.6-18V	9 0 2 1 3 3 0 3
10W 350mA 1-10V dim	101.5-51-29.5	14-28V	9 0 2 2 3 4 0 1
10W 350mA phase-cut dim	102-38-21	12-28V	9 0 2 2 3 4 0 2
10W 350mA	115-41-25	13-26V	9 0 2 2 3 4 0 6
14W 350mA	145-33-21	2.5-42V	9 0 2 4 3 5 0 1
17W 350mA 10-49V DALI	108-52-22	10-49V	9 0 2 4 3 6 0 1