



**WEVER & DUCRÉ**  
LIGHTING

# MATCH 2.0

190251B5

Project

Type

Notes

Quantity

Date

## GENERAL

Ceiling , Semi-Recessed

Tilt max 90°

Rotation 350°

Black Matt

RAL 9005<sup>a</sup>

IP20

IC rated

Interior

Output: 1090 lm

CIE flux code: 97 100 100 100 100

## LED

3000 K

CRI ≥ 90

L80 / 50000h

2 SDCM

## OPTICAL

Beam angle 30°

## ELECTRICAL

excl. driver

18 V

LED Inset 6.1 W

Total insets 12.2 W

Class 3

700 mA

## PHYSICAL

Length 26 mm

Width 125 mm

Height 117 mm

0.27 kg

wire springs

## CUTOUT

Length 105 mm


Width 30 mm

Min. ceiling thickness 4 mm


Max. ceiling thickness 26 mm

Recessed depth 60 mm

<sup>a</sup> Color may deviate slightly due to production conditions.



Ceiling recessed luminaire with 2 spotlights; made from die-cast aluminium with base; surface Black Matt; powder coated, matt texture; RAL 9005; installation without tools using wire springs; suitable for ceiling thickness of 4-26 mm; recessed depth 60 mm; with COB (Chip on Board) technology for maximum efficiency; light colour 3000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; beam angle 30°; spotlight head 350° rotatable and 90° tiltable; degree of protection IP20; PC3; IC rated; driver not included; light source replaceable by an authorized professional;






WEVER & DUCRÉ  
LIGHTING

# MATCH 2.0

190251B5

## LIGHT DISTRIBUTION



## CONE DIAGRAM

700mA 30°

h (m)	E0° (lx)	ø (m)
1	1580	0.54
2	390	1.09
3	180	1.63
4	100	2.18
5	60	2.72

## ELECTRICAL

### Driver

TYPE	L · W · H (MM)	VOLTAGE	ORDERCODE
15W   700mA   12-20V   phase-cut dim	122 · 41 · 23	12-20V	9 0 2 2 5 5 0 2
28W   700mA	143 · 43 · 30	6-40V	9 0 2 4 5 7 0 4
28W   700mA   3-40V   DALI	136 · 42,5 · 24	3-40V	9 0 2 4 5 8 0 1