



WEVER & DUCRÉ
LIGHTING

MATCH SURFACE 2.0

177254B3

Project
Type
Notes
Quantity
Date

GENERAL

Ceiling , Surface
 Tilt max 90°
 Rotation 350°
 Black Matt
 RAL 9005^a
 IP20
 Interior
 Output: 1090 lm
 CIE flux code: 97 100 100 100 100

LED

2700 K
 CRI ≥ 90
 L80 / 50000h
 2 SDCM

OPTICAL

Beam angle 30°

ELECTRICAL

phase-cut dim
 220 - 240 V
 Total connected power 17.5 W
 Class 1


PHYSICAL

Length 200 mm
 Width 26 mm
 Height 117 mm
 0.42 kg


^a Color may deviate slightly due to production conditions.



Ceiling surface luminaire with 2 spotlights; made from die-cast aluminium; surface Black Matt; powder coated, matt texture; RAL 9005; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 2700 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; beam angle 30°; 350° rotatable and 90° tiltable; degree of protection IP20; PCI; driver included; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;



LIGHT DISTRIBUTION



[177254B3] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré apply.
 © Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com



WEVER & DUCRÉ
LIGHTING

MATCH SURFACE 2.0

177254B3

CONE DIAGRAM

31°

h (m)	E0° (lx)	ø (m)
1	1510	0.56
2	380	1.12
3	170	1.67
4	90	2.23
5	60	2.79