



WEVER & DUCRÉ
LIGHTING

MATCH WALL 4.0

377464B3

Project

Type

Notes

Quantity

Date

GENERAL

Wall , Surface

Black Matt

RAL 9005^a

IP20

Interior

Indirect 770 lm

Direct 770 lm

Total 1540 lm

CIE flux code: 99 100 100 48 100

LED

2700 K

CRI ≥ 90

L80 / 50000h

2 SDCM

OPTICAL

Beam angle 23°

ELECTRICAL

phase-cut dim

220 - 240 V

Total connected power 22.8 W

Class 1

PHYSICAL

Diameter 69 mm


Height 720 mm

0.76 kg

^a Color may deviate slightly due to production conditions.



Tubular wall surface luminaire made from aluminium; surface Black Matt; powder coated, matt texture; RAL 9005; up and down light emission; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 2700 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90 ; beam angle 23°; 220 - 240 V; degree of protection IP20; PC1; UGR ≤ 10 ; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° ≤ 3000 cd/m²; driver included; light source replaceable by an authorized professional; control gear replaceable by end-user;





WEVER & DUCRÉ
LIGHTING

MATCH WALL 4.0

377464B3

LIGHT DISTRIBUTION

