



WEVER & DUCRÉ
LIGHTING

PIRRO petit 2.0

129151B3

Project

Type

Notes

Quantity

Date

GENERAL

Ceiling , Recessed

Black Matt

RAL 9005^a

IP20

IC rated

Interior

Output: 290 lm

CIE flux code: 98 100 100 100 100

LED

2700 K

CRI ≥ 90

L80 / 50000h

3 SDCM

OPTICAL

Beam angle 28°

ELECTRICAL

excl. driver

12 V

LED Inset 3.8 W

Class 3

350 mA

PHYSICAL

Length 66 mm

Width 40 mm

Height 40 mm

0.07 kg

wire springs

CUTOUT

Length 64 mm



Width 33 mm

Min. ceiling thickness 4 mm


Max. ceiling thickness 25 mm

Recessed depth 60 mm

^a Color may deviate slightly due to production conditions.



Rectangular ceiling recessed downlight made from die-cast aluminium; surface Black Matt; RAL 9005; installation without tools using wire springs; suitable for ceiling thickness of 4-25 mm; recessed depth 60 mm; with COB (Chip on Board) technology for maximum efficiency; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; beam angle 28°; degree of protection IP20; PC3; IC rated; UGR ≤ 13; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° ≤ 3000 cd/m²; driver not included; light source replaceable by an authorized professional;






WEVER & DUCRÉ
LIGHTING

PIRRO petit 2.0

129151B3

LIGHT DISTRIBUTION



CONE DIAGRAM

25°

h (m)	E0° (lx)	ø (m)
1	1120	0.45
2	280	0.90
3	120	1.35
4	70	1.81
5	40	2.26

ELECTRICAL

Driver

TYPE	L · W · H (MM)	ORDERCODE
4.5W 350 mA 8-12V phase-cut dim IP44	49 · 30 · 20	9 0 2 2 3 1 0 1