



WEVER & DUCRÉ
LIGHTING

PIRRO

petit 6.0

129351B3

Project
Type
Notes
Quantity
Date

GENERAL

Ceiling , Recessed
 Black Matt
 RAL 9005^a
 IP20
 IC rated
 Interior
 Output: 870 lm
 CIE flux code: 98 100 100 100 100

LED

2700 K
 CRI ≥ 90
 L80 / 50000h
 3 SDCM

OPTICAL

Beam angle 28°

ELECTRICAL

excl. driver
 36 V
 LED Inset 11.4 W
 Class 3
 350 mA


PHYSICAL

Length 172 mm
 Width 40 mm
 Height 40 mm
 0.15 kg
 wire springs


CUTOUT

Length 168 mm
 Width 33 mm
 Min. ceiling thickness 4 mm
 Max. ceiling thickness 25 mm
 Recessed depth 60 mm

^a Color may deviate slightly due to production conditions.



Rectangular ceiling recessed downlight made from die-cast aluminium; surface Black Matt; RAL 9005; installation without tools using wire springs; suitable for ceiling thickness of 4-25 mm; recessed depth 60 mm; with COB (Chip on Board) technology for maximum efficiency; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; beam angle 28°; degree of protection IP20; PC3; IC rated; UGR ≤ 13; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° ≤ 3000 cd/m²; driver not included; light source replaceable by an authorized professional;






WEVER & DUCRÉ
LIGHTING

PIRRO

petit 6.0

129351B3

LIGHT DISTRIBUTION



CONE DIAGRAM

25°

h (m)	E0° (lx)	ø (m)
1	3370	0.45
2	840	0.90
3	370	1.35
4	210	1.81
5	130	2.26

ELECTRICAL

Driver

TYPE	L · W · H (MM)	VOLTAGE	ORDERCODE
15W 350 mA 27-42V phase-cut dim	102·49·29	27-42V	9 0 2 2 3 4 0 3
14.7W 350mA 26-42V	122·41·23	26-42V	9 0 2 2 3 5 0 4