



WEVER & DUCRÉ
LIGHTING

PIRRO

petit SURFACE 12.0

129954B3

Project

Type

Notes

Quantity

Date

GENERAL

Ceiling, Surface

Black Matt

RAL 9005^a

IP20

Interior

Output: 1740 lm

CIE flux code: 98 100 100 100 100

LED

2700 K

CRI \geq 90

L80 / 50000h

3 SDCM

OPTICAL

Beam angle 28°

ELECTRICAL

phase-cut dim

220 - 240 V

Total connected power 26.8 W

Class 1

PHYSICAL

Length 322 mm

Width 31 mm


Height 50 mm

0.38 kg

^a Color may deviate slightly due to production conditions.



Rectangular ceiling surface mounted downlight made from die-cast aluminium; surface Black Matt; RAL 9005; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 2700 K; binning initial MacAdam \leq 3 SDCM; CRI \geq 90; beam angle 28°; degree of protection IP20; PC1; UGR \leq 13; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° \leq 3000 cd/m²; driver included; light source replaceable by an authorized professional; control gear replaceable by end-user;






WEVER & DUCRÉ
LIGHTING

PIRRO

petit SURFACE 12.0

129954B3

LIGHT DISTRIBUTION



CONE DIAGRAM

25°

h (m)	E0° (lx)	ø (m)
1	6740	0.45
2	1690	0.90
3	750	1.35
4	420	1.81
5	270	2.26