



WEVER & DUCRÉ
LIGHTING

PLANO SURFACE 1.0 PAR16

118520E0

Project
Type
Notes
Quantity
Date

GENERAL

Ceiling , Surface
 Tilt max 30°
 Rotation 355°
 White Matt + Black Matt
 IP20
 Interior
 Output: 465^a, 505^b lm
 CIE flux code: 94 98 100 100 92

LED

Lamp PAR16
 Socket GU10
 max. per socket 12.0 W
 CRI ≥ 90


ELECTRICAL

100 - 240 V
 LED Inset 6.5 W
 Class 1


PHYSICAL

Length 150 mm
 Width 84 mm
 Height 120 mm
 1.39 kg


^a PAR16 LAMP 2700K CRI90
^b PAR16 LAMP 3000K CRI90



Rectangular ceiling surface mounted downlight with 1 spot made from die-cast aluminium; surface White Matt + Black Matt; powder coated, matt texture + wet painted, matt smooth; lamp socket GU10; lamp type PAR16; max. 12W; 100 - 240 V; 355° rotatable and 30° tiltable; degree of protection IP20; PC1; lamp not included;



LIGHT DISTRIBUTION



[118520E0] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré apply.
 © Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com



WEVER & DUCRÉ
LIGHTING

PLANO SURFACE 1.0 PAR16

118520E0

LAMPS

PAR16 LED Lamp

TYPE	COLOUR	Ø·H (MM)	ORDERCODE
2700K >90 CRI GU10	Black	∅50·60	9 0 1 2 2 8 B 3
3000K >90 CRI GU10	Black	∅50·60	9 0 1 2 2 8 B 5
2700K >90 CRI GU10	White	∅50·60	9 0 1 2 2 8 W 3
3000K >90 CRI GU10	White	∅50·60	9 0 1 2 2 8 W 5
2700K >80 CRI GU10	Silver	∅50·60	9 0 5 2 2 7 S 2
3000K >80 CRI GU10	Silver	∅50·60	9 0 5 2 2 7 S 4