



WEVER & DUCRÉ
LIGHTING

REVER DINING 2.0

655284B2

Project

Type

Notes

Quantity

Date

GENERAL

Table
Standing
Signal Black
IP23
Interior
135 lm
9004^a

LED

2700 K
CRI 80
L80 / 50000 h
3-step binning

OPTICAL

Opal
Beam angle 111°


PHYSICAL

Length 180 mm
Width 135 mm
Height 320 mm
0.93 kg
black cable plug with transformer


ELECTRICAL

touch dim
220 - 240 V
Total connected power 1.8 W
PC2

^a RAL Palette colors may deviate slightly due to production conditions.



LIGHT DISTRIBUTION





WEVER & DUCRÉ
LIGHTING

REVER DINING 2.0

655284B2

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.96	0.93	0.89	0.85	0.82
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.