



WEVER & DUCRÉ
LIGHTING

ROOMOR CABLE 1.2 PAR16

248120BB2

Project

Type

Notes

Quantity

Date

GENERAL

Ceiling

Suspended

Jet Black

Jet Black

Jet Black

IP20

Interior

405 lm

RAL 9005^a

LED

Lamp PAR16

PAR16

Socket GU10

max. 15 W

CRI \geq 90

OPTICAL

Shade 2.0

PHYSICAL

Diameter 250 mm

Height 295 mm

1.07 kg

incl. 2.5 m suspension

ELECTRICAL

100 - 240 V

Total connected power 6.5 W


Class 1

Safety distance 0.3 m


^a Color may deviate slightly due to production conditions.



Suspended luminaire made from aluminium; surface Jet Black wet painted; matt texture; RAL 9005; incl. 2.5 m suspension; cable and ceiling base in Jet Black; shade Jet Black; wet painted; matt texture; lamp socket GU10; lamp type PAR16; max. 15W; 100 - 240 V; degree of protection IP20; PC1; lamp not included;



LIGHT DISTRIBUTION





WEVER & DUCRÉ
LIGHTING

ROOMOR CABLE 1.2 PAR16

248120BB2

SHADE 2.0

Shade 2.0

TYPE	COLOUR	Ø·H (MM)	ORDERCODE
ROOMOR	Black	∅250·150	9 1 1 3 6 2 0 B 1
ROOMOR	Black	∅250·150	9 1 1 3 6 2 0 K 1
ROOMOR	Grey	∅250·150	9 1 1 3 6 2 F T 1
ROOMOR	Grey	∅250·150	9 1 1 3 6 2 G W 1
ROOMOR	Red	∅250·150	9 1 1 3 6 2 R W 1

SHADE 1.0

Shade 1.0

TYPE	COLOUR	Ø·H (MM)	ORDERCODE
ROOMOR	Black	∅205·70	9 1 1 3 6 1 0 B 1
ROOMOR	Black	∅205·70	9 1 1 3 6 1 0 K 1
ROOMOR	Grey	∅205·70	9 1 1 3 6 1 F T 1
ROOMOR	Grey	∅205·70	9 1 1 3 6 1 G W 1
ROOMOR	Red	∅205·70	9 1 1 3 6 1 R W 1

SHADE 3.0

Shade 3.0

TYPE	COLOUR	Ø·H (MM)	ORDERCODE
ROOMOR	Black	∅405·15	9 1 1 3 6 3 0 B 1
ROOMOR	Black	∅405·150	9 1 1 3 6 3 0 K 1
ROOMOR	Grey	∅405·150	9 1 1 3 6 3 F T 1
ROOMOR	Grey	∅405·150	9 1 1 3 6 3 G W 1
ROOMOR	Red	∅405·150	9 1 1 3 6 3 R W 1

SHADE 4.0

Shade 4.0

TYPE	COLOUR	Ø·H (MM)	ORDERCODE
ROOMOR	Black	∅510·75	9 1 1 3 6 4 0 B 1
ROOMOR	Black	∅510·75	9 1 1 3 6 4 0 K 1
ROOMOR	Grey	∅510·75	9 1 1 3 6 4 F T 1
ROOMOR	Grey	∅510·75	9 1 1 3 6 4 G W 1
ROOMOR	Red	∅510·75	9 1 1 3 6 4 R W 1

LAMPS

PAR16 LED Lamp

TYPE	COLOUR	Ø·H (MM)	ORDERCODE
2700K >90 CRI GU10	Black	∅50·58	9 0 1 2 2 8 B 3
3000K >90 CRI GU10	Black	∅50·58	9 0 1 2 2 8 B 5
2700K >90 CRI GU10	White	∅50·58	9 0 1 2 2 8 W 3
3000K >90 CRI GU10	White	∅50·58	9 0 1 2 2 8 W 5
2700K >80 CRI GU10	Silver	∅50·52	9 0 5 2 2 7 S 2
3000K >80 CRI GU10	Silver	∅50·52	9 0 5 2 2 7 S 4