



WEVER & DUCRÉ
LIGHTING

ROOMOR CABLE 1.3 PAR16

248120BF3

GENERAL

Ceiling
Suspended
Jet Black
Jet Black
Felt Grey
IP20
Interior
450 lm
RAL 9005^a

LED

Lamp PAR16
PAR16
Socket GU10
max. 15 W
CRI \geq 90

OPTICAL

Shade 3.0

PHYSICAL

Diameter 405 mm
Height 295 mm
1.44 kg
incl. 2.5 m suspension

ELECTRICAL


100 - 240 V
Total connected power 6.5 W
Class 1
Safety distance 0.3 m

^a Color may deviate slightly due to production conditions.


Project
Type
Notes
Quantity
Date



Suspended luminaire made from aluminium; surface Jet Black wet painted; matt texture; RAL 9005; incl. 2.5 m suspension; cable and ceiling base in Jet Black; shade Felt Grey; lamp socket GU10; lamp type PAR16; max. 15W; 100 - 240 V; degree of protection IP20; PC1; lamp not included;



LIGHT DISTRIBUTION





WEVER & DUCRÉ
LIGHTING

ROOMOR CABLE 1.3 PAR16

248120BF3

SHADE 2.0

Shade 2.0

TYPE	COLOUR	Ø·H (MM)	ORDERCODE
ROOMOR	Black	∅250-150	9 1 1 3 6 2 0 B 1
ROOMOR	Black	∅250-150	9 1 1 3 6 2 0 K 1
ROOMOR	Grey	∅250-150	9 1 1 3 6 2 F T 1
ROOMOR	Grey	∅250-150	9 1 1 3 6 2 G W 1
ROOMOR	Red	∅250-150	9 1 1 3 6 2 R W 1

SHADE 1.0

Shade 1.0

TYPE	COLOUR	Ø·H (MM)	ORDERCODE
ROOMOR	Black	∅205-70	9 1 1 3 6 1 0 B 1
ROOMOR	Black	∅205-70	9 1 1 3 6 1 0 K 1
ROOMOR	Grey	∅205-70	9 1 1 3 6 1 F T 1
ROOMOR	Grey	∅205-70	9 1 1 3 6 1 G W 1
ROOMOR	Red	∅205-70	9 1 1 3 6 1 R W 1

SHADE 3.0

Shade 3.0

TYPE	COLOUR	Ø·H (MM)	ORDERCODE
ROOMOR	Black	∅405-15	9 1 1 3 6 3 0 B 1
ROOMOR	Black	∅405-150	9 1 1 3 6 3 0 K 1
ROOMOR	Grey	∅405-150	9 1 1 3 6 3 F T 1
ROOMOR	Grey	∅405-150	9 1 1 3 6 3 G W 1
ROOMOR	Red	∅405-150	9 1 1 3 6 3 R W 1

SHADE 4.0

Shade 4.0

TYPE	COLOUR	Ø·H (MM)	ORDERCODE
ROOMOR	Black	∅510-75	9 1 1 3 6 4 0 B 1
ROOMOR	Black	∅510-75	9 1 1 3 6 4 0 K 1
ROOMOR	Grey	∅510-75	9 1 1 3 6 4 F T 1
ROOMOR	Grey	∅510-75	9 1 1 3 6 4 G W 1
ROOMOR	Red	∅510-75	9 1 1 3 6 4 R W 1

LAMPS

PAR16 LED Lamp

TYPE	COLOUR	Ø·H (MM)	ORDERCODE
2700K >90 CRI GU10	Black	∅50-58	9 0 1 2 2 8 B 3
3000K >90 CRI GU10	Black	∅50-58	9 0 1 2 2 8 B 5
2700K >90 CRI GU10	White	∅50-58	9 0 1 2 2 8 W 3
3000K >90 CRI GU10	White	∅50-58	9 0 1 2 2 8 W 5
2700K >80 CRI GU10	Silver	∅50-52	9 0 5 2 2 7 S 2
3000K >80 CRI GU10	Silver	∅50-52	9 0 5 2 2 7 S 4