

STRANGE 2.0 PAR16

131220M0

Project
Туре
Notes
Quantity
Date

GENERAL
Ceiling
Recessed
Tilt min 35°
Tilt max 35°
Rotation 355°
Champagne
IP20
Interior
LED
Lamp 2 x PAR16
PAR16
Socket GU10
max. 12 W
OPTICAL
Wide Flood
Wide Flood
ELECTRICAL
ELECTRICAL 100 - 240 V
100 - 240 V
100 - 240 V Class 2
100 - 240 V Class 2
100 - 240 V Class 2 Safety distance 0.3 m
100 - 240 V Class 2 Safety distance 0.3 m
100 - 240 V Class 2 Safety distance 0.3 m PHYSICAL Length 140 mm
100 - 240 V Class 2 Safety distance 0.3 m PHYSICAL Length 140 mm Width 70 mm
100 - 240 V Class 2 Safety distance 0.3 m PHYSICAL Length 140 mm Width 70 mm Height 115 mm 0.7 kg
100 - 240 V Class 2 Safety distance 0.3 m PHYSICAL Length 140 mm Width 70 mm Height 115 mm 0.7 kg CUTOUT
100 - 240 V Class 2 Safety distance 0.3 m PHYSICAL Length 140 mm Width 70 mm Height 115 mm 0.7 kg CUTOUT Length 156 mm
100 - 240 V Class 2 Safety distance 0.3 m PHYSICAL Length 140 mm Width 70 mm Height 115 mm 0.7 kg CUTOUT Length 156 mm Width 86 mm
100 - 240 V Class 2 Safety distance 0.3 m PHYSICAL Length 140 mm Width 70 mm Height 115 mm 0.7 kg CUTOUT Length 156 mm Width 86 mm Min. ceiling thickness 8 mm
100 - 240 V Class 2 Safety distance 0.3 m PHYSICAL Length 140 mm Width 70 mm Height 115 mm 0.7 kg CUTOUT Length 156 mm Width 86 mm



□ - ↓ ↓ ▲ § ← 0,3 → D

Rectangular ceiling recessed luminaire made from aluminium; surface Champagne; wet painted; smooth semi glossy; recessed depth 120 mm; lamp socket GU10; lamp type PAR16; 2x max. 12W; 100 - 240 V; 355° rotatable and 35° tiltable; degree of protection IP20; PC2; lamp not included;



September 1, 2022