



WEVER & DUCRÉ
LIGHTING

SWAM 2.0

746378K3

Project

Type

Notes

Quantity

Date

GENERAL

Wall
Surface
Jet Black + Gold
RAL 9005^a
IP65
Exterior
Indirect 250 lm
Direct 420 lm
Total 670 lm

LED

2700 K
CRI ≥ 90

OPTICAL

Opal


ELECTRICAL

phase-cut dim
220 - 240 V
Total connected power 13.1 W
Class 1
Safety distance 0.3 m


PHYSICAL

Length 185 mm
Width 213 mm
Height 110 mm
0.95 kg


^a Color may deviate slightly due to production conditions.



Wall surface luminaire made from die-cast aluminium; surface Jet Black + Gold; powder coated and wet painted; matt texture; RAL 9005; up and down light emission; PCB 3-step binning; phase-cut dim; light colour 2700 K; CRI 90; 220 - 240 V; degree of protection IP65; PC1; light source replaceable by an authorized professional;



LIGHT DISTRIBUTION



[746378K3] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.
© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com



WEVER & DUCRÉ
LIGHTING

SWAM 2.0

746378K3