



WEVER & DUCRÉ  
LIGHTING

# TAIO ROUND IP65 1.0

180181G5

Project
Type
Notes
Quantity
Date

## GENERAL

Ceiling  
 Recessed  
 Gold  
 IP65  
 Interior  
 335<sup>a</sup> to 455<sup>b</sup> lm

## LED

3000 K

## OPTICAL

Flood

## PHYSICAL

Diameter 77 mm  
 Height 55 mm  
 0.13 kg  
 wire springs

## ELECTRICAL

excl. power supply  
 18 V  
 Total connected power 6<sup>a</sup> to 9<sup>b</sup> W  
 LED Inset 6<sup>a</sup> to 9<sup>b</sup> W  
 PC3  
 Safety distance 0.3 m


## CUTOUT

Diameter 70 mm  
 Min. ceiling thickness 4 mm  
 Max. ceiling thickness 27 mm  
 Recessed depth 70 mm

<sup>a</sup> 350mA  
<sup>b</sup> 500mA



IP65





WEVER & DUCRÉ  
LIGHTING

# TAIO ROUND IP65 1.0

180181G5

## ELECTRICAL

### Power Supply

TYPE	L · W · H (MM)	ORDERCODE
Driver 17W   350mA   2-49V   IP68	122·54·26	9 0 2 1 3 6 0 2
Driver 24W   500mA   2-49V   IP68	122·54·26	9 0 2 1 4 7 0 2