



**WEVER & DUCRÉ**  
LIGHTING

# TRACE WALL 2.0

333264B3

Project .....

Type .....

Notes .....

Quantity .....

Date .....

## GENERAL

Wall , Surface .....

Black Matt .....

RAL 9005<sup>a</sup> .....

IP20 .....

Interior .....

Indirect 500 lm .....

Direct 500 lm .....

Total 1000 lm .....

CIE flux code: 92 98 99 50 100 .....

## LED

2700 K .....

CRI  $\geq$  90 .....

L80 / 50000h .....

2 SDCM .....

## OPTICAL

Medium , Beam angle 22° .....

## ELECTRICAL

phase-cut dim .....

220 - 240 V .....

Total connected power 15.0 W .....

Class 1 .....

## PHYSICAL

Length 70 mm .....

Width 80 mm .....


Height 180 mm .....

0.74 kg .....


<sup>a</sup> Color may deviate slightly due to production conditions.



Wall surface luminaire made from aluminium; surface Black Matt; powder coated; matt texture; RAL 9005; up and down light emission; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 2700 K; binning initial MacAdam  $\leq$  2.SDCM; CRI  $\geq$  90; 220 - 240 V; degree of protection IP20; PCI; driver included; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;



## LIGHT DISTRIBUTION



[333264B3] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré apply.  
© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com



WEVER & DUCRÉ  
LIGHTING

# TRACE WALL 2.0

333264B3