



WEVER & DUCRÉ
LIGHTING

TRAIN NARROW 1.0

719143D4

Project

Type

Notes

Quantity

Date

GENERAL

Wall
Surface
Dark Grey Texture
IP65
Exterior
120 lm

LED

3000 K
CRI 80
L90 / 50000 h
3-step binning

OPTICAL


Narrow Up or Narrow Down
Beam angle 46°x5°

PHYSICAL


Length 48 mm
Width 48 mm
Height 96 mm
0.24 kg

ELECTRICAL


incl. power supply
220 - 240 V
Total connected power 6 W
PC1
Safety distance 0.3 m



IP65



LIGHT DISTRIBUTION



[719143D4] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BVBA apply.
© Wever & Ducré BVBA · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com



WEVER & DUCRÉ
LIGHTING

TRAIN NARROW 1.0

719143D4