



WEVER & DUCRÉ
LIGHTING

TRAM 1.0

747368B5

Project

Type

Notes

Quantity

Date

GENERAL

Ceiling

Surface

Jet Black

RAL 9005^a

Below IP65

Exterior

415 lm

LED

3000 K

CRI \geq 90

3-step binning

OPTICAL

Beam angle 38°

ELECTRICAL

phase-cut dim

220 - 240 V

Total connected power 6 W

Class 1

Safety distance 0.3 m


PHYSICAL

Diameter 50 mm


Height 75 mm

0.24 kg


^a Color may deviate slightly due to production conditions.



Cylindrical ceiling surface mounted downlight made from die-cast aluminium; surface Jet Black; powder coated; matt texture; RAL 9005; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; binning initial MacAdam 3 SDCM; CRI 90; 220 - 240 V; degree of protection IP65; PC1; light source not replaceable;



LIGHT DISTRIBUTION






WEVER & DUCRÉ
LIGHTING

TRAM 1.0

747368B5

CONE DIAGRAM

38°



h (m)	E0° (lx)	ø (m)
1	854	0.69
2	214	1.38
3	95	2.06
4	53	2.75
5	34	3.44