



**WEVER & DUCRÉ**  
LIGHTING

# TRAM WALL 2.0

747268A5

Project

Type

Notes

Quantity

Date

## GENERAL

Wall  
Surface  
Anthracite Grey  
RAL 7016<sup>a</sup>  
Below IP65  
Exterior  
Indirect 255 lm  
Direct 255 lm  
Total 510 lm

## LED

3000 K  
CRI  $\geq$  90  
3-step binning


## ELECTRICAL

phase-cut dim  
220 - 240 V  
Total connected power 7.9 W  
Class 1  
Safety distance 0.3 m


## PHYSICAL

Diameter 50 mm  
Height 105 mm  
0.3 kg


<sup>a</sup> Color may deviate slightly due to production conditions.



Cylindrical wall surface mounted luminaire made from die-cast aluminium; surface Anthracite Grey; powder coated; matt texture; RAL 7016; up and down light emission; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; binning initial MacAdam 3 SDCM; CRI 90; 220 - 240 V; degree of protection IP65; PC1; light source not replaceable;



## LIGHT DISTRIBUTION





WEVER & DUCRÉ  
LIGHTING

# TRAM WALL 2.0

747268A5