



WEVER & DUCRÉ
LIGHTING

TUBE 1.0 PAR16

734120D0

Project
Type
Notes
Quantity
Date

GENERAL

Ceiling
Surface
Dark Grey Texture
Below IP65
Exterior
355 ^a to 360 ^b lm

LED

Lamp PAR16
PAR16
Socket GU10
max. 5 W
CRI ≥ 80

OPTICAL

Beam angle 38°

ELECTRICAL

phase-cut dim
100 - 240 V
Total connected power 4.1 ^b to 4.8 ^a W
Class 1
Safety distance 0.3 m

PHYSICAL

Diameter 80 mm
Height 105 mm
0.6 kg


^a PAR16 LED LAMP 3000 K CRI90 GU10

^b PAR16 LED LAMP 2700 K CRI90 GU10




IP65 $\leq 0,3 \rightarrow \text{D}$

Cylindrical ceiling surface mounted downlight made from die-cast aluminium; surface Dark Grey Texture; powder coated; matt texture; lamp socket GU10; lamp type PAR16; max. 5W; 100 - 240 V; degree of protection IP65; PC1; lamp not included;



LIGHT DISTRIBUTION





WEVER & DUCRÉ
LIGHTING

TUBE 1.0 PAR16

734120D0

CONE DIAGRAM

PAR16 LED LAMP 38°
3000 K CRI90 GU10

h (m)	E0° (lx)	ø (m)
1	640	0.68
2	160	1.37
3	71	2.05
4	40	2.74
5	26	3.42

LAMPS

PAR16 LED Lamp

TYPE	Ø·H (MM)	ORDERCODE
2700K >80 CRI GU10	ø50·52	9 0 5 2 2 7 S 2
3000K >80 CRI GU10	ø50·52	9 0 5 2 2 7 S 4