



WEVER & DUCRÉ
LIGHTING

TUBE WALL 1.0 PAR16

711120A0

Project
Type
Notes
Quantity
Date

GENERAL

Wall
 Surface
 Anthracite Grey
 IP65
 Exterior
 355^a to 360^b lm

LED

Lamp PAR16
 PAR16
 Socket GU10
 max. 5 W

OPTICAL

Beam angle 38°

PHYSICAL

Diameter 80 mm
 Height 80 mm
 0.52 kg


ELECTRICAL

100 - 240 V
 Total connected power 4.1^b to 4.8^a W
 PC1
 Safety distance 0.3 m


^a LED 2700K CRI 80 silver
^b LED 3000K CRI 80 silver



IP65



LIGHT DISTRIBUTION



[711120A0] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BVBA apply.
 © Wever & Ducré BVBA · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com



WEVER & DUCRÉ
LIGHTING

TUBE WALL 1.0 PAR16

711120A0

CONE DIAGRAM

LED 2700K CRI ≥ 80 Silver

h (m)	EO° (lx)	ø (m)
1	640	0.68
2	159	1.37
3	71	2.05
4	40	2.74
5	25	3.42

ELECTRICAL

PAR16 LED Lamp

TYPE	Ø · H (MM)	ORDERCODE
2700K >80 CRI GU10	ø51-55	9 0 5 2 2 7 S 2
3000K >80 CRI GU10	ø51-55	9 0 5 2 2 7 S 4
2700K GU10		9 0 5 2 2 8 S 2