



WEVER & DUCRÉ
LIGHTING

WIRO WALL 1.8

3345E0B0

Project
Type
Notes
Quantity
Date

GENERAL

Wall
 Surface
 Black Steel
 IP20
 Interior
 245 lm

LED


Lamp T30
 E27
 Socket E27
 max. 25.0 W
 CRI \geq 90

ELECTRICAL


220 - 240 V
 Total connected power 5.0 W
 Class 1
 Safety distance 0.3 m

PHYSICAL


Diameter 187 mm
 Height 288 mm
 1.9 kg
 cable base



Wall luminaire; shade made from varnished steel; lamp socket E27; lamp type T30; 220 - 240 V; degree of protection IP20; PC1; lamp not included;



LIGHT DISTRIBUTION



[3345E0B0] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.
 © Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com



WEVER & DUCRÉ
LIGHTING

WIRO WALL 1.8

3345E0B0

LAMPS

T30-225 LED Lamp

TYPE	Ø · H (MM)	ORDERCODE
2200K E27	ø30-225	9 0 0 3 E 1 2 9
2700K E27	ø30-225	9 0 0 3 E 1 3 6

OPTIONAL

Cable Wall Bracket

TYPE	Ø · H (MM)	ORDERCODE
only for WIRO textile cable	ø30-21	9 0 0 5 2 0 6 2

Strain Relief

TYPE	Ø · H (MM)	ORDERCODE
for suspended luminaire power cable fixation in base	ø12.5-13	9 0 0 5 2 0 6 4