



WEVER & DUCRÉ
LIGHTING

X-BEAM 1.0

700374A4

Project
Type
Notes
Quantity
Date

GENERAL

Floor , Standing
 Tilt max 110°
 Anthracite Grey
 RAL 7016 ^a
 IP65
 Exterior
 Output: 1680 lm
 CIE flux code: 49 76 90 0 100

LED

3000 K
 CRI ≥ 80
 L80 / 60000h
 3 SDCM

OPTICAL

Super Wide Flood , Beam angle 108°
 UGR < 10
 ≥1500 cd/m²


ELECTRICAL

phase-cut dim
 220 - 240 V
 Total connected power 24.3 W
 Class 2


PHYSICAL

Length 130 mm
 Width 130 mm
 Height 35 mm
 1.22 kg


^a Color may deviate slightly due to production conditions.



Rectangular outdoor floor or wall projector; surface Anthracite Grey; powder coated; matt texture; RAL 7016; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80; 220 - 240 V; 110° tiltable; beam angle 108°; degree of protection IP65; PC2; driver included; optional ground spike available; optional snoot in Black Matt available; light source not replaceable; control gear replaceable by end-user;



LIGHT DISTRIBUTION



[700374A4] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré apply.
 © Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com



WEVER & DUCRÉ
LIGHTING

X-BEAM

1.0

700374A4

MOUNTING

Ground Spike

TYPE	Ø · H (MM)	ORDERCODE
X-BEAM	∅43 · 212	9 0 0 1 3 1 1 5

OPTICAL

Snoot

TYPE	L · W · H (MM)	ORDERCODE
X-BEAM	138 · 45 · 138	9 0 0 1 9 0 2 3