



WEVER & DUCRÉ
LIGHTING

X-BEAM ROUND 1.0

700474A4

Project

Type

Notes

Quantity

Date

GENERAL

Floor , Standing

Tilt max 110°

Anthracite Grey

RAL 7016 ^a

IP65

Exterior

Output: 1680 lm

LED

3000 K

CRI ≥ 80

3 SDCM

OPTICAL

Super Wide Flood , Beam angle 108°

ELECTRICAL

phase-cut dim

220 - 240 V

Total connected power 25.0 W

Class 2

PHYSICAL




Diameter 160 mm

Height 35 mm


1.3 kg

^a Color may deviate slightly due to production conditions.



IP65   

Round outdoor floor or wall projector; surface Anthracite Grey; powder coated; matt texture; RAL 7016; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80; 220 - 240 V; 110° tiltable; beam angle 108°; degree of protection IP65; PC2; driver included; optional ground spike available; optional snoot in Black Matt available;





WEVER & DUCRÉ
LIGHTING

X-BEAM ROUND 1.0

700474A4

MOUNTING

Ground Spike

TYPE	Ø · H (MM)	ORDERCODE
X-BEAM	∅43 · 212	9 0 0 1 3 1 1 5

OPTICAL

Snoot round

TYPE	L · W (MM)	ORDERCODE
X-BEAM	∅166 · 45	9 0 0 1 9 0 3 1