



Valena™ Life - Valena™ INMATIC
Rotary dimmer 300 W RLC + LEDs

Cat. No(s): 7 521 60 - 7 522 60 - 7 523 60
 7 520 60 - 7 563 60



7 521 60 - 7 522 60 - 7 523 60



7 520 60

1. USE

Rotary dimming for all types of lamps.
 Can be associated with one or several push buttons, for ON/OFF or dimming control.
 Integrates memory level function: the light switches ON the same level it has been switched OFF.
 Soft-start and soft-stop lighting (2 s).
 Mechanisms to be equipped with plates.
 Screw or claw mounting.

2. RANGE


Rotary dimmer 300 W - 2-wires - Supplied with support frame and rocker plate

White	Ivory	Aluminium	Black	Without rocker
7 521 60	7 522 60	7 523 60	7 563 60	-

Rotary dimmer 300 W - 2-wires - Supplied with support frame

White	Ivory	Aluminium	Black	Without rocker
-	-	-	-	7 520 60

3. OVERALL DIMENSIONS (mm)




References	A	B	C	D
7 521 60 - 7 522 60 - 7 523 60 - 7 563 60	75	75	32	21.5
7 520 60	75	75	32	19.5

4. CONNECTION


4 terminals with screws
 Terminal capacity: 2 x 2.5 mm²
 Stripping length: 8 mm

5. INSTALLATION

Simple



With push buttons



6. TECHNICAL CHARACTERISTICS

■ 6.1 Mechanical characteristics

Protection against solid bodies and liquids: IP 40
 Protection against impact: IK 02

■ 6.2 Material characteristics

Polygloss appearance
 Colour: - White RAL 9003
 - Ivory RAL 1013
 - Aluminium
 - Black

Material: - Front cover: Polycarbonate
 - Halogen-free
 - UV-resistant

Material of the support: - Polycarbonate grey RAL 7037
 - Halogen-free

Self-extinguishing:

850°C/30 s for insulating components holding live parts in place
 650°C/30 s for other insulating components.


















■ 6.3 Electrical characteristics

Voltage: 100 to 240 V~

Frequency: 50-60 Hz


Standby consumption: 0.2 W

■ Load table

		R		L		C/L			
				^(*)  + 	^(*) 	 +  + 			
									
200 V / 240 V	Max.	300 W	300 W	300 VA	300 VA	300 VA	300 VA	75 W or 10 lamps max.	75 W or 10 lamps max.
	Min.	5 W	5 W	5 VA	5 VA	5 VA	5 VA	5 W	5 W
100 V / 200 V	Max.	150 W	150 W	150 VA	150 VA	150 VA	150 VA	37 W or 10 lamps max.	37 W or 10 lamps max.
	Min.	5 W	5 W	5 VA	5 VA	5 VA	5 VA	5 W	5 W

(*)Use only with transformers designed to function with electronic switches.

■ Setting C or L



■ 6.4 Climate characteristics

Storage temperature: - 10°C to + 70°C

Usage temperature: 0°C to + 35°C

7. MAINTENANCE

Surface cleaning with a cloth.

Do not use: acetone, tar remover, trichloroethylene.

Maintenance with the following products: Hexane (EN 60669-1), Methylated spirit, Soapy water, Diluted ammonia, Bleach diluted to 10%, Window-cleaning products, Pre-impregnated-wipes.

Caution: Always test before using other special cleaning products.

8. STANDARDS AND APPROVALS

Compliant with installation and manufacturing standards.

See e. catalogue.