



LIGHT SOURCE

LED 5.19W
 2200K-3000K | 500 lm | CRI 90
 220-240 VAC/50Hz
 Phase cut dim
 or
 E14 max. 40W | 250V
 (light bulb not included)

PRODUCT USE

Indoor IP20

MATERIALS

Shade: Blown glass
 Suspension: black anodized steel and aluminium

FINISH

blue - brown - green - white

REFERENCE CODE

SHADE EXCL. SUSPENSION

S	brown	20AXLE001500031
S	blue	20AXLE001500048
S	white	20AXLE001500161
S	green	20AXLE001500233
M	brown	20AXLE001600031
M	blue	20AXLE001600048
M	white	20AXLE001600161
M	green	20AXLE001600233
L	brown	20AXLE002100031
L	blue	20AXLE002100048
L	white	20AXLE002100161
L	green	20AXLE002100233

SUSPENSION

LED	2m cable	20AXLE0020LED01
LED	5m cable	20AXLE0050LED01
E14	4m cable	20AXLE0040E1401

E14 LIGHT SOURCES (RECOMMENDED)

LED 45 - LED Filament E14	20FILAMENTLED45
LED 25 - LED Filament E14	20FILAMENTLED25
4.5W 2700K 450lm CRI90	
Dimmable	

Canopy 3 White RAL9016	20PLAF030000001
Canopy 3 Black RAL9005	20PLAF030000040
Canopy 5 White RAL 9016	20PLAF050000001
Canopy 5 Black RAL 9005	20PLAF050000040

