

CHART ASYM

25-Sep.-2017

1.2

LED 10W | 220-240VAC | 50-60Hz | COB 3-step | incl. PS | phase-cut dim

CE IP67 0.3m

3000K | >80CRI | 600lm

inox

75255714

OPTIONAL
recessed housing

90012203

1.6

LED 15W | 220-240VAC | 50-60Hz | COB 3-step | incl. PS | phase-cut dim

CE IP67 0.3m

3000K | >80CRI | 850lm



inox

75265714

OPTIONAL
recessed housing

90012204

with recessed housing



OPTIONAL, (ORDER SEPARATELY)
recessed housing




CHART ASYM 1.2







CHART ASYM 1.6

DIMENSIONS



MOUNTING INSTRUCTION

- Remove the protective foam inside of the CHART ASYM. Make sure to screw the screws back on, crosswise, to ensure IP67
- Make a hole in the ground according to the prescribed dimensions (of the recessed housing)
- Drainage: we recommend that all exterior groundspots should be installed with a drainage level even when using a recessed housing



POWER CONNECTION

- Exterior: WATERPROOF Connection



Remark: Do not open or cut off the Water Stopper on cable.

- MOUNTING WITH RECESSED HOUSING

Use the bolts and the nuts to attach the CHART ASYM to the recessed housing



Caution, risk of electric shock

The light source of the integrated LED is not replaceable; When the light source reaches its end of life the whole luminaire shall be replaced.



WEVER & DUCRÉ
LIGHTING

www.weverducre.com

Wever & Ducre bvba Kwadestraat 153 bus 2.1 8800 Roeselare

INSTALLATION
INSTRUCTIONS

PAGE 1/2

CHART ASYM

25-Sep.-2017

1.2

LED 10W | 220-240VAC | 50-60Hz | COB 3-step | incl. PS | phase-cut dim

CE IP67 0.3m

3000K | >80CRI | 600lm

inox

75255714

OPTIONAL
recessed housing

90012203

1.6

LED 15W | 220-240VAC | 50-60Hz | COB 3-step | incl. PS | phase-cut dim

CE IP67 0.3m

3000K | >80CRI | 850lm

inox


75265714

OPTIONAL
recessed housing


90012204

without recessed housing

A. Attached to the floor (or wall, for wall mounting)




B. Rests on the stainless steel borders of the fixture




A. Attached to the floor (or wall, for wall mounting)

- ⑤ Use the screws to attach the CHART ASYM to the floor or wall. Make sure to measure correctly so that you can screw onto a hard material.



B. Rests on the stainless steel borders of the fixture

- ⑤ Place the CHART ASYM into the hole, no tools needed to fix it into the hole. Just let it rest on the stainless steel borders of the fixture



Caution, risk of electric shock
The light source of the integrated LED is not replaceable;
When the light source reaches its end of life the whole luminaire shall be replaced.