

MIRBI IP44 ceiling recessed

17-Aug.-2019

1.0 LED

LED 7W | 220-240VAC | PCB 3-step | phase-cut dim

CE □ IP44 ↓0.3m P

3000K | >90CRI | 440lm

□ clear / opal PMMA

11458805

2.0 LED

LED 7W | 220-240VAC | PCB 3-step | phase-cut dim

CE □ IP44 ↓0.3m P

3000K | >90CRI | 440lm

□ clear / opal PMMA

11468805

OPTIONAL

plaster kit (for 1.0)

plaster kit (for 2.0)


recessed housing (for 1.0 or 2.0)

90017101


90017102

90012026

①



③



DIMENSIONS


1.0



2.0




MOUNTING INSTRUCTION

- ① Make a hole in the ceiling according to the prescribed dimensions.
- ② **POWER CONNECTION**
for 1.0 or 2.0

- ③ Insert the fixture in the hole optionally with plaster kit or recessed housing combined with plaster kit.

General mounting notice for ceiling / wall with optional plaster kit or recessed


PLASTER KIT

Use for brick walls or plastered stalon




PLASTER KIT

Use for brick walls or plastered stalon



RECESSED HOUSING

Use in concrete structures: always in combination with plaster kit.



The light source of the integrated LED is not replaceable.



Caution, risk of electric shock



WEVER & DUCRÉ
LIGHTING

www.weverducre.com

Wever & Ducré bvba Spinnerijstraat 99/21 8500 Kortrijk

**INSTALLATION
INSTRUCTIONS**