



WEVER & DUCRÉ
LIGHTING

BENTA 3.6

310274B5

GENERAL

Wall

Surface

Jet Black

IP20

Interior

Indirect 165 lm

Direct 170 lm

Total 335 lm

9005^a

LED

3000 K

CRI 90

L90 / 50000 h

3-step binning

OPTICAL

Wide Flood

PHYSICAL

Length 360 mm

Width 130 mm

Height 46 mm

1.3 kg

ELECTRICAL

incl. PS | phase-cut dim

220 - 240 V

Total connected power 8 W

PC1

0.3 m

^a RAL Palette colors may deviate slightly due to production conditions.


Project

Type


Notes

Quantity

Date



LIGHT DISTRIBUTION



Project

Type

Notes

Quantity

Date

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.98	0.98	0.97	0.97
LSF	1	1	1	1	1

MF	LMF × RSMF × LLMF × LSF		RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor		LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor		LSF	Lamp Survival Faktor

^a According to “CIE 97, Maintenance of indoor electric lighting systems”, 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.