



WEVER & DUCRÉ  
LIGHTING

# BENTO 3.6

309374B5

## GENERAL

Wall  
Surface  
Jet Black  
IP20  
Interior  
Indirect 165 lm  
Direct 170 lm  
Total 335 lm  
9005<sup>a</sup>

## LED

3000 K  
CRI 90  
L90 / 50000 h  
3-step binning

## OPTICAL

Wide Flood

## PHYSICAL


Length 360 mm  
Width 130 mm  
Height 46 mm  
1.5 kg

## ELECTRICAL


incl. PS | phase-cut dim  
220 - 240 V  
Total connected power 8 W  
PC1  
0.3 m

<sup>a</sup> RAL Palette colors may deviate slightly due to production conditions.

Project  
Type  
Notes  
Quantity  
Date



## LIGHT DISTRIBUTION





WEVER & DUCRÉ  
LIGHTING

# BENTO 3.6

309374B5

Project \_\_\_\_\_

Type \_\_\_\_\_

Notes \_\_\_\_\_

Quantity \_\_\_\_\_

Date \_\_\_\_\_

## Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.98	0.98	0.97	0.97
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF <sup>a</sup>	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF <sup>a</sup>	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

<sup>a</sup> According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.