



WEVER & DUCRÉ
LIGHTING

BOX SUSPENDED 3.0 PAR16

214220B0

Project

Type

Notes

Quantity

Date

GENERAL

Ceiling

Suspended

Jet Black

IP20

Interior

440^a to 445^b lm

RAL 9005 ^c

LED

Lamp PAR16

PAR16

Socket GU10

max. 12 W

CRI 80

OPTICAL

Beam angle 48°

PHYSICAL

Length 67 mm

Width 67 mm

Height 300 mm

0.76 kg

incl. 2.5 m suspension

ELECTRICAL

100 - 240 V

Total connected power 6.6^b to 6.7^a W

PC1

Safety distance 0.3 m


^a LED 3000K CRI 80 white

^b LED 2700K CRI 80 white


^c RAL Palette colors may deviate slightly due to production conditions.



Squared ceiling suspended luminaire made from die-cast aluminium; surface Jet Black; powder coated; matt texture; RAL 9005; inclusive adjustable cable suspension max. 2500mm in Signal Black; lamp socket GU10; lamp type PAR16; max. 12W; 100 - 240 V; degree of protection IP20; PC1; lamp not included; ceiling base not included;



LIGHT DISTRIBUTION





WEVER & DUCRÉ
LIGHTING

BOX SUSPENDED 3.0 PAR16

214220B0

CONE DIAGRAM

LED 3000K CRI ≥ 88 white

h (m)	EO° (lx)	ø (m)
1	618	0.89
2	155	1.78
3	69	2.67
4	39	3.56
5	25	4.45

LED LAMPS


PAR16 LED Lamp

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
2700K >90 CRI GU10	Jet Black	ø50 · 58	9 0 1 2 2 8 B 3
3000K >90 CRI GU10	Jet Black	ø50 · 58	9 0 1 2 2 8 B 5
2700K >80 CRI GU10	Signal White	ø50 · 58	9 0 1 2 2 8 W 2
2700K >90 CRI GU10	Signal White	ø50 · 58	9 0 1 2 2 8 W 3
3000K >80 CRI GU10	Signal White	ø50 · 58	9 0 1 2 2 8 W 4

SUSPENSION OPTIONS

Invisible Ceiling Suspension System

COLOUR	L · W (MM)	ORDERCODE
Signal Black	140 · 66	9 0 0 1 5 1 9 5
Pure White	140 · 66	9 0 0 1 5 1 9 6



Single Suspension

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
Ceiling Base round	Signal Black	ø84 · 29	9 0 0 5 2 0 2 1
Ceiling Base round	Pure White	ø84 · 29	9 0 0 5 2 0 2 2



Single Ceiling Base

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
semi recessed	Pure White	ø84 · 72	9 0 0 5 2 0 2 6
semi recessed	Signal Black	ø84 · 72	9 0 0 5 2 0 2 7

