



WEVER & DUCRÉ  
LIGHTING

# CITY 1.6

115184W5

## GENERAL

Ceiling

Recessed

Signal White

IP44

Interior

840 lm

9003<sup>a</sup>

## LED

3000 K

3-step binning

## PHYSICAL

Diameter 210 mm

Height 47 mm

0.64 kg

## ELECTRICAL

phase-cut dim

220 - 240 V

Total connected power 13 W

65 lm/W

PC1

0.3 m

## CUTOUT

Diameter 202-205 mm

Min. ceiling thickness 4 mm

Max. ceiling thickness 22 mm

Recessed depth 50 mm

<sup>a</sup> RAL Palette colors may deviate slightly due to production conditions.

Project

Type


Notes

Quantity

Date



IP44   





WEVER & DUCRÉ  
LIGHTING

# CITY 1.6

115184W5

Project

---

Type

---

Notes

---

Quantity

---

Date

---

## Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.95	0.93	0.9	0.88
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF <sup>a</sup>	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF <sup>a</sup>	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

<sup>a</sup> According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.