



WEVER & DUCRÉ  
LIGHTING

# CONE 1.0

200184B2

## GENERAL

Ceiling  
Suspended  
Jet Black  
IP20  
Interior  
468 lm  
9005<sup>a</sup>

## LED

2700 K  
CRI 90  
L90 / 50000 h  
3-step binning

## PHYSICAL


Diameter 45 mm  
Height 270 mm  
0.55 kg

## ELECTRICAL


phase-cut dim  
220 - 240 V  
Total connected power 7.9 W  
59 lm/W  
PC1  
0.3 m

<sup>a</sup> RAL Palette colors may deviate slightly due to production conditions.

Project  
Type  
Notes  
Quantity  
Date



## LIGHT DISTRIBUTION





WEVER & DUCRÉ  
LIGHTING

# CONE 1.0

200184B2

Project

---

Type

---

Notes

---

Quantity

---

Date

---

## Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.98	0.98	0.98	0.97
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF <sup>a</sup>	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF <sup>a</sup>	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

<sup>a</sup> According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

## FIXATION

### Strain Relief

TYPE	Ø · H (MM)	ORDERCODE
for multi base   without steel wire	ø12.5 · 13	9 0 0 5 2 0 2 3