

WEVER & DUCRÉ
LIGHTING

CORK

1.0

210163B2

GENERAL

Ceiling
Suspended
Jet Black
IP20
Interior
180 lm
9005^a

LED

2700 K
3-step binning

PHYSICAL

Diameter 82 mm
0.24 kg

ELECTRICAL

incl. power supply
120 - 240 V
Total connected power 3 W
PC1
0.3 m

^a RAL Palette colors may deviate slightly due to production conditions.


Project _____

Type _____

Notes _____

Quantity _____

Date _____



Project

Type

Notes

Quantity

Date

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	1.0	0.95	0.91	0.87	0.83
LSF	1	1	1	1	1
MF	LMF × RSMF × LLMF × LSF		RSMF ^a	Room Surface Maintenance Factor	
MF	Maintenance Factor		LLMF	Lamp Lumens Maintenance Factor	
LMF ^a	Luminaire Maintenance Factor		LSF	Lamp Survival Faktor	

^a According to “CIE 97, Maintenance of indoor electric lighting systems”, 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

OPTICAL

Bottle 1

TYPE	Ø · H (MM)	ORDERCODE
CORK	ø75 · 174	9 0 0 1 9 0 1 3

Bottle 2

TYPE	Ø · H (MM)	ORDERCODE
CORK	ø87 · 323	9 0 0 1 9 0 1 4