



WEVER & DUCRÉ
LIGHTING

DEEP ADJUST 2.0 PAR16

112720B0

Project

Type

Notes

Quantity

Date

GENERAL

Ceiling

Recessed

Jet Black

IP20

Interior

642 lm

9005^a

LED

Lamp 2 x PAR16

PAR16

Socket GU10

Max. power 12 W

2700 K

CRI 90

OPTICAL

Wide Flood

Beam angle 48°

PHYSICAL

Length 182 mm

Width 94 mm

Height 102 mm

0.42 kg

Standard Springs

Tilt min 35°

Tilt max 35°

Rotation 355°

ELECTRICAL

100 - 240 V

Total connected power 15 W

43 lm/W

PC2

0.3 m

CUTOUT

Length 87 mm



Width 176 mm

Min. ceiling thickness 4 mm


Max. ceiling thickness 23 mm

Recessed depth 105 mm

^a RAL Palette colors may deviate slightly due to production conditions.



LIGHT DISTRIBUTION





WEVER & DUCRÉ
LIGHTING

DEEP ADJUST 2.0 PAR16

112720B0

CONE DIAGRAM

wide flood 48°

h (m)	E0° (lx)	ø (m)
1	903	0.89
2	226	1.78
3	100	2.67
4	56	3.56
5	36	4.45

LED LAMPS

PAR16 LED Lamp

TYPE	COLOUR	Ø-H (MM)	ORDERCODE
2700K GU10	Jet Black	ø50-58	9 0 1 2 2 8 B 3
3000K GU10	Jet Black	ø50-58	9 0 1 2 2 8 B 5
2700K GU10	Signal White	ø50-58	9 0 1 2 2 8 W 2
2700K GU10	Signal White	ø50-58	9 0 1 2 2 8 W 3
3000K GU10	Signal White	ø50-58	9 0 1 2 2 8 W 4
4000K GU10	Signal White	ø50-58	9 0 1 2 2 8 W 6

PAR16 LED Lamp | Ambient

TYPE	Ø-H (MM)	ORDERCODE
1800-2850K GU10	ø50-58	9 0 1 2 2 9 S 9